

## Specification Sheet

Part Number: T150L9X2



Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Natural, 25/pkg

Article Number	111-15419
Type	T150L
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none"><li>•Engineered and manufactured for maximum performance and quality.</li><li>•Made from 100% high-quality plastic to ensure efficient recycling.</li><li>•Inside serration for a strong grip onto bundles.</li><li>•Easy application either manually or with a tensioning tool.</li><li>•Bent tail allows for simpler insertion.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Natural, 25/pkg
<b>Global Part Name</b>	T150L-PA66-NA
<b>Minimum Tensile Strength (Imperial)</b>	175.0
<b>Minimum Tensile Strength (Metric)</b>	780.0
<b>Length L (Imperial)</b>	32.3
<b>Length L (Metric)</b>	820.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.35
<b>Width W (Metric)</b>	8.9
<b>Bundle Diameter Min (Imperial)</b>	0.32
<b>Bundle Diameter Min (Metric)</b>	8.0
<b>Bundle Diameter Max (Imperial)</b>	9.6
<b>Bundle Diameter Max (Metric)</b>	243.8

<b>Thickness T (Imperial)</b>	0.079
-------------------------------	-------

**Thickness T (Metric)** 2

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

**Material Shortcut** PA66

<b>US MIL SPEC</b>	MS3367-6-9	<b>Flammability</b>
--------------------	------------	---------------------

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Certification/Specification WEB**

UL | ANSI/UL 1565 UL | ANSI/UL 62275 UL | ANSI/UL 746B

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

<b>Package Quantity(Imperial)</b>	25
-----------------------------------	----

**Package Quantity (Metric)** 25

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

16