



Model: USB-4COMi-M

4-Port RS-422 / 485 USB to Serial Adapter

A 4-Port RS-422, RS-485 adapter for serial communication that utilizes four external DIP switches for easy access to the signal used. Automatic transmit and receive control for 2-wire RS-485 half-duplex mode.



Specifications

Serial Interface	RS422/485 port
Ports	4
Speed	Up to 921.6kbps, 12 Mbps, full-speed USB
Signals	RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
USB Interface	USB 2.0
Power	External power supply 5V DC required. Adapter included, 12V not possible.
Driver	Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in)
Connectors	4 DB9 male, terminal blocks for RS422/485
Dimensions	167 x 99 x 29 mm (WxLxH), 189 x 102 x 30 mm with DB9 connector and ears
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features	Product Information	
<ul style="list-style-type: none"> • DIN-Rail mountable • 4 x RS422/485 ports • Speed up to 921.6kbps • No external power supply • Metal case 	Product Name:	USB-4COMi-M
	Packing List:	USB-4COMi-M, USB cable 0,9m, Power Adapter, CD, English Documentation
	Optional Accessories:	N/A