


**Notes:**

1. Only RoHS Compliant Processes and Materials used for this assembly.
2. Marking to Contain "ConductRF", Date Code & Part No., Black Text.
3. Single Centered Marker on Cables of 6" and longer
4. Sweep Tested to validate Max VSWR @ Max Freq.
5. Store Hi-Point Data.

**ConductRF(wk/yr)  
V3A33-PGFPMF-xxx**


**Marker Example**



CRF #	Length	Typ. Insertion Loss(dB)		
		6GHz	12GHz	18GHz
S06	6"	0.82	1.16	1.42
S08	8"	1.00	1.42	1.74
S12	12"	1.36	1.93	2.37
S16	16"	1.73	2.45	3.01
S24	24"	2.45	3.49	4.28
VSWR Max.		1.50:1		

**Part No. Configurator - XXX**

FXX = Length in Feet (eg F03=3ft)  
SXX = Length in Inches (eg S18=18")  
XXM = Length in Meters (eg 2M5=2.5m)  
CXX = Length in CM (eg C50=50cm)



5	Strain relief	Shrink Tube	Black
4	Label marker	Shrink Tube	White
3	Cable - Low Loss Flex	A33RFJ	FEP Black
2	SMPS Female for Backplane	PGF13A-A33G01	Gold
1	SMPM Female	PMF11B-A33G01	Gold
ITEM	DESCRIPTION	MATERIALS	FINISH

REV.	DESCRIPTION	ECN	DRAWN	DATE	Customer DWG	Title: VITA67.3 SMPS Backplane Contact to SMPM Female on 0.047" Flex Cbl.			
2	Updated Length Ref.		DG	02/17/21	Remarks: 07/035/5	Originated: 02/11/21	Conduct RF sales@ConductRF.com Tel: +1 978 374 6840	Range: VITA Sheet 1 of 1	
1	Pre-Release		DG	02/11/21			Dwg Ref: V3A33-PGFPMF		
					Length Tolerances: ≤24" = ±0.25" >24" = ± 1%	Checked: JW	Approved: PL	Rev: 2	
REVISION HISTORY								Part No: <b>V3A33-PGFPMF-XXX</b>	