



THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



	ISSUE NUMBER	
ORIGIN	IAL	

(1)





NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

DIELECTRIC

**OPERATING TEMPERATURE:** 

WITHSTANDING VOLTAGE:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED




30A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX. **INSULATOR RESISTANCE:** 

5000MΩ min.

-55°C ~ 125°C

1000V AC rms

	SW REFERENCE NO.: 629 COMBO ASSEMBLY			
COMBIN	DRAWN: C.B	DATE: JAN. 01/20	19	
			DATE:	
EDAC IN	C THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
TORONTO, O CANAD	NTARIOSHALL NOT BE REPRODUCED, OR COPIEDQOR USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-17W2240-3T1		ISSUE
YOUR CONNECTION TO QUALITY & SE	RVICE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 629-17W	2240-3T1	1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

