

CleanBlast™ HFE-Based Cleaning Fluid

Product Features:

- For use with *VIAMI SOLUTIONS® CLEANBLAST* fiber end-face cleaning systems
- Cleans dust, lint, oil & grit from fiber end-faces
- High-purity, optic-grade cleaning solvent
- Suitable for use with *CLEANBLAST* benchtop and portable systems
- 225ml bottle provides approx. 8,000 cleanings; 3.8L bottle provides approx. 128,000 cleanings
- Nonflammable
- Leaves no residue

The *CLEANBLAST* HFE-Based Cleaning Fluid is packaged specifically for use in the *VIAMI SOLUTIONS CLEANBLAST* fiber end-face cleaning system. This fast-drying solvent cleans dust, lint, polishing grit, oil and fingerprints.

Engineered to be a drop-in replacement, this product is *VIAMI* factory approved for use with the *CLEANBLAST* cleaning system and uses the same chemistry to ensure compliance with validated manufacturing processes. It is double filtered and packaged to permit the standard spill-resistant *CLEANBLAST* machine refill process.

Compatible with all *VIAMI CLEANBLAST* cleaning tips and suitable for cleaning SC, FC, ST, LC, MU, E2000 and MPO/MTP connectors. Leaves no residue.

Nonflammable and fast evaporating, this cleaning fluid ships as non hazardous/not regulated by all modes of transport, including air freight.

NOTE: This product is a direct replacement solvent for use with the following *VIAMI SOLUTIONS CLEANBLAST* model numbers:

FCL-P1005 FCL-P1000 FCL-P2000
FCL-P1005-EU FCL-P1000-EU



FCLP-SOL1
7.61 oz / 225ml

FCLP-SOL1-XL
1 gallon / 3.8 L

Technical Details	
Odor	Slight, Ether
Boiling Point	45°C/113°F
Chemical family	HFC
Percent Volatile	100
Vapor Pressure @ 20°C	360 mmHG (@25°C)
Non Volatile Residue (% by volume)	<0.010
Health, Safety, and Environmental Data	
Flashpoint	None
Flammable	No
NFPA	Health: 3 Flammability: 1 Instability: 0
Organic Content	889 g/l (@20°C)
RoHS and WEEE Compliant	Yes
GHS/ICS Pictogram	
Packaging	
Single Bottle - 7.61oz / 225mL	FCLP-SOL1
Pack of 6 Bottles (Each Bottle - 7.61oz / 225mL)	FCLP-SOL1-6
Single Bottle - 1 Gallon / 3.8L	FCLP-SOL1-XL