## ATGBICS FTLX8574D3BNL Finisar Compatible Transceiver SFP+ 10GBase-SR (850nm, MMF, 400m, DOM)

Brand: ATGBICS Product code: FTLX8574D3BNL-C

**Product name :** FTLX8574D3BNL Finisar Compatible Transceiver SFP+ 10GBase-SR (850nm, MMF, 400m, DOM)



FTLX8574D3BNL Finisar Compatible Transceiver SFP+ 10GBase-SR (850nm, MMF, 400m, DOM, Ext Temp)

ATGBICS FTLX8574D3BNL Finisar Compatible Transceiver SFP+ 10GBase-SR (850nm, MMF, 400m, DOM):

ATGBICS FTLX8574D3BNL 10GBase-SR supports a distance of up to 400m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Finisar FTLX8574D3BNL= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 10000 Mbit/s  Interface type * SFP+  Single-mode fiber (SMF) supported  X	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W	
	e fiber (MMF) supported connector LC eiver standard stransfer distance th 850 nm AN AN Interface type 10 Gigabit Ethernet	Operational conditions	
Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type		Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 °C 85 °C -5 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
Digital Diagnostics Monitoring		Weight & dimensions	
(DDM)		Width	13.4 mm
Wavelength-division multiplexing (WDM)	×	Depth Height	56.5 mm 8.5 mm
Features		Weight	19 g
Product colour Housing material Plug and Play Hot-Plug support	sing material Metal and Play	Packaging data  Number of products included  Package type	1 pc(s) Box
Hot-swap	<b>V</b>	Technical details	
Easy to install Country of origin Brand compatibility Certification	China Finisar CE, FCC, RoHS	Sustainability compliance Sustainability certificates Doesn't contain	RoHS Lead



5056468761149

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.