

## Coaxial Cable Connector 11\_MBX-50-2-1/113\_N

### Description

Straight cable plug

Interface standards  
HUBER+SUHNER MBX



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 6 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.003546 kg

#### Environmental Data

Operating temperature -55 °C to 155 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze / Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00162030  
Catalogue drawing DCA-00161650  
Assembly instruction DOC-0000333519

### Ordering Information

Bulk 100 pcs package 11\_MBX-50-2-1/113\_NH  
Single package 11\_MBX-50-2-1/113\_NE

### Additional Information

Suitable cables ENVIROFLEX\_316\_D, K\_02252\_D, G\_02232\_D