



NOTES

- 適合ターミナルシリーズ: 503657シリーズ
APPLICABLE TERMINAL : 503657 SERIES
- 嵌合相手 : 504056シリーズ
MATE WITH : 504056SERIES
- △ 偶数極に適用
APPLY FOR EVEN CIRCUIT.
- △ キャビティ番号 : 1桁から2桁の数字にて表示。
金型番号 : アルファベット1文字にて表示
CAVITY NO. : 1 TO 2 DIGIT NUMBER
MOLD NO. : 1 LETTER ON ALPHABET
- 本製品のプラスチック部に黒点等が確認される場合や、色合いが異なる場合がございますが、製品性能に影響はございません。
THERE IS NO INFLUENCE IN THE PRODUCT PERFORMANCE THOUGH THE BLACK SPOT ETC. MIGHT BE CONFIRMED TO THE PLASTIC PART OF THIS PRODUCT AND THE SHADE MIGHT BE DIFFERENT.
- ELV 及びRoHS適合品
ELV AND RoHS COMPLIANT

18	23.2	504054-2000	504054-**00	20
B	A	ORDER NO.	CONNECTOR SERIES NO.	CKT

PROPOSED EC NO: J2012-0149 DRWN:TKON CHKD: APPR:NUKITA 2011/07/08 2011/08/10 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS		THIRD ANGLE PROJECTION	
			MM ONLY		5:1	METRIC			
	10 UNDER	±0.2	DRAWN BY	DATE	TITLE				
	10 OVER 30 UNDER	±0.25	TKON	2011/07/08	2.0 W/B CONN. DUAL REC. CRIMP HSG				
	30 OVER	±0.3	CHECKED BY	DATE					
	ANGULAR ±1 °	APPROVED BY	DATE	MOLEX INCORPORATED					
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	NUKITA	2011/08/10	DOCUMENT NO. SD-504054-001					
		MATERIAL NO. SEE TABLE		SHEET NO. 1 OF 1					
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

PART	MATERIAL
HOUSING	POLYESTER (PBT), UL94V-0 COLOR : NATURAL(WHITE)