

Ordering Information	
Part Number	Contact Area Plating Finish
K85X-EA-9S	Gold Flash (standard)
K85X-EA-9S-15	15u" Gold (15 option)
K85X-EA-9S-30	30u" Gold (30 option)

### Material and Finish

Shell: steel, Nickel plated  
 Insulator: PBT with glass-fiber reinforcement, UL 94V-0 rated, color-black

Contact Material:

Socket - brass

Contact Plating:

Standard:

Gold flash on mating end, tin on termination end, with entire contact nickel underplated

-15 Option:

15u" gold on mating end, tin on termination end, with entire contact nickel underplated

-30 Option:

30u" gold on mating end, tin on termination end, with entire contact nickel underplated

### Electrical Specifications

Rated Current: 2A

Rated Voltage: 30V RMS

Withstanding Voltage:

500V (rms) AC for 1 minute

Insulation Resistance:

more than 1000 Megohm at 500V DC

Contact Resistance:

13 milliohm max.

Dielectric Strength:

1000V for 1 minute

Operating Temperature:

-55°C to +105°C

RoHS COMPLIANT




Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	02/14/06	New Drawing	R. Aguirre	H. MA	R. Aguirre	02/14/06
A2	1/9/08	ECO #07-052	WILL H.	H. MA		
A3	09/16/10	Add Hole Dim.	S. Vien	H. MA		
A4	12/31/17	ECO #17-030	G. Serrato	C. Furumasu		

**K85X-EA-9S**

Vertical Soldercup Mount D-Sub

9 pin female, RoHS Compliant



UNITS  
mm