

R71VN4150GY30M

Aliases (71VN4150GY30M)

R71, Film, Metallized Polypropylene, General Purpose, 1.5 uF, 20%, 520 VDC, 105°C, Lead Spacing = 22.5mm



Click [here](#) for the 3D model.

Dimensions

| | |
|----|--------------------|
| L | 26.5mm +0.3/-0.5mm |
| H | 20mm +0.1/-0.5mm |
| T | 11mm +0.2/-0.5mm |
| S | 22.5mm +/-0.4mm |
| H0 | 18.5mm +/-0.5mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----|
| Packaging | T&R |
| Packaging Quantity | 160 |

General Information

| | |
|------------------|--|
| Series | R71 |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | PFC and Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Component Weight | 3.4 g |
| Miscellaneous | Above 105C DC And AC Voltage Derating Is 4%/C. |

Specifications

| | |
|-----------------------|---|
| Capacitance | 1.5 uF |
| Capacitance Tolerance | 20% |
| Voltage AC | 250 VAC |
| Voltage DC | 520 VDC |
| Temperature Range | -40/+110°C |
| Rated Temperature | 105°C |
| Dissipation Factor | 0.1% 25C |
| Insulation Resistance | 20 GOhms |
| Max dV/dt | 120 V/us |
| Resistance | 63.7 mOhms (100kHz) |
| Ripple Current | 2.02 Amps (100kHz 85C), 180 Amps (Peak) |
| Inductance | 18 nH |