

TENSILITY

End of Life Notification

October 3, 2017

EOL issue number: 00001

Product Type: DIN and Mini DIN Cables

Tensility announces plans to obsolete the items below. We will not be able to accept LTB (last time buy) orders for this item. Custom orders meeting the MOQ for these items are available.

Products affected by change:

Part Number	Part Description
10-00419	Cable, 1830 mm, 3P mini-DIN male 50-00156, to stripped tinned, 20 AWG, UL2464 30-00023, shielded
10-00420	Cable, 1830 mm, 4P mini-DIN male 50-00157, to stripped tinned, 20 AWG, UL2464 30-00024, shielded
10-00421	Cable, 1830 mm, 5P mini-DIN male 50-00158, to stripped tinned, 20 AWG, UL2464 30-00025, shielded
10-00422	Cable, 1830 mm, 6P mini-DIN male 50-00159, to stripped tinned, 20 AWG, UL2464 30-00026, shielded
10-00423	Cable, 1830 mm, 7P mini-DIN male 50-00160, to stripped tinned, 20 AWG, UL2464 30-00027, shielded
10-00424	Cable, 1830 mm, 8P mini-DIN male 50-00161, to stripped tinned, 20 AWG, UL2464 30-00028, shielded
10-00425	Cable, 1830 mm, 9P mini-DIN male 50-00162, to stripped tinned, 20 AWG, UL2464 30-00029, shielded
10-00426	Cable, 1830 mm, 3P mini-DIN female 50-00163, to stripped tinned, 20 AWG, UL2464 30-00023, shielded
10-00427	Cable, 1830 mm, 4P mini-DIN female 50-00164, to stripped tinned, 20 AWG, UL2464 30-00024, shielded
10-00428	Cable, 1830 mm, 5P mini-DIN female 50-00165, to stripped tinned, 20 AWG, UL2464 30-00025, shielded
10-00429	Cable, 1830 mm, 6P mini-DIN female 50-00166, to stripped tinned, 20 AWG, UL2464 30-00026, shielded
10-00430	Cable, 1830 mm, 7P mini-DIN female 50-00167, to stripped tinned, 20 AWG, UL2464 30-00027, shielded
10-00431	Cable, 1830 mm, 8P mini-DIN female 50-00168, to stripped tinned, 20 AWG, UL2464 30-00028, shielded
10-00432	Cable, 1830 mm, 9P mini-DIN female 50-00169, to stripped tinned, 20 AWG, UL2464 30-00029, shielded
10-00433	Cable, 1830 mm, 3P DIN male 50-00170, to stripped tinned, 20 AWG, UL2464 30-00023, shielded
10-00434	Cable, 1830 mm, 4P DIN male 50-00171, to stripped tinned, 20 AWG, UL2464 30-00024, shielded
10-00435	Cable, 1830 mm, 5P DIN male 50-00172, to stripped tinned, 20 AWG, UL2464 30-00025, shielded
10-00436	Cable, 1830 mm, 6P DIN male 50-00173, to stripped tinned, 20 AWG, UL2464 30-00026, shielded
10-00437	Cable, 1830 mm, 7P DIN male 50-00174, to stripped tinned, 20 AWG, UL2464 30-00027, shielded
10-00438	Cable, 1830 mm, 8P DIN male 50-00175, to stripped tinned, 20 AWG, UL2464 30-00028, shielded
10-00439	Cable, 1830 mm, 13P DIN male 50-00176, to stripped tinned, 20 AWG, UL2464 30-00033, shielded
10-00440	Cable, 1830 mm, 3P DIN female 50-00177, to stripped tinned, 20 AWG, UL2464 30-00023, shielded
10-00441	Cable, 1830 mm, 4P DIN female 50-00178, to stripped tinned, 20 AWG, UL2464 30-00024, shielded
10-00442	Cable, 1830 mm, 5P DIN female 50-00179, to stripped tinned, 20 AWG, UL2464 30-00025, shielded
10-00443	Cable, 1830 mm, 6P DIN female 50-00180, to stripped tinned, 20 AWG, UL2464 30-00026, shielded
10-00444	Cable, 1830 mm, 7P DIN female 50-00181, to stripped tinned, 20 AWG, UL2464 30-00027, shielded
10-00445	Cable, 1830 mm, 8P DIN female 50-00182, to stripped tinned, 20 AWG, UL2464 30-00028, shielded
10-00446	Cable, 1830 mm, 13P DIN female 50-00183, to stripped tinned, 20 AWG, UL2464 30-00033, shielded
10-00525	Cable, 1830 mm, 3P 90° DIN male 50-00170, to stripped tinned, 26 AWG, UL2464 30-00060, shielded
10-00526	Cable, 1830 mm, 4P 90° DIN male 50-00171, to stripped tinned, 26 AWG, UL2464 30-00061, shielded
10-00527	Cable, 1830 mm, 5P 90° DIN male 50-00172, to stripped tinned, 26 AWG, UL2464 30-00062, shielded
10-00528	Cable, 1830 mm, 6P 90° DIN male 50-00173, to stripped tinned, 26 AWG, UL2464 30-00063, shielded
10-00529	Cable, 1830 mm, 7P 90° DIN male 50-00174, to stripped tinned, 26 AWG, UL2464 30-00064, shielded
10-00530	Cable, 1830 mm, 8P 90° DIN male 50-00175, to stripped tinned, 26 AWG, UL2464 30-00065, shielded

TENSILITY

10-00531	Cable, 1830 mm, 13P 90° DIN male 50-00176, to stripped tinned, 26 AWG, UL2464 30-00059, shielded
10-00532	Cable, 1830 mm, 3P 90° DIN female 50-00177, to stripped tinned, 26 AWG, UL2464 30-00060, shielded
10-00533	Cable, 1830 mm, 4P 90° DIN female 50-00178, to stripped tinned, 26 AWG, UL2464 30-00061, shielded
10-00534	Cable, 1830 mm, 5P 90° DIN female 50-00179, to stripped tinned, 26 AWG, UL2464 30-00062, shielded
10-00535	Cable, 1830 mm, 6P 90° DIN female 50-00180, to stripped tinned, 26 AWG, UL2464 30-00063, shielded
10-00536	Cable, 1830 mm, 7P 90° DIN female 50-00181, to stripped tinned, 26 AWG, UL2464 30-00064, shielded
10-00537	Cable, 1830 mm, 8P 90° DIN female 50-00182, to stripped tinned, 26 AWG, UL2464 30-00065, shielded
10-00538	Cable, 1830 mm, 13P 90° DIN female 50-00183, to stripped tinned, 26 AWG, UL2464 30-00059, shielded
10-00539	Cable, 1830 mm, 3P 90° mini-DIN male 50-00156, to stripped tinned, 26 AWG, UL2464 30-00060, shielded
10-00540	Cable, 1830 mm, 4P 90° mini-DIN male 50-00157, to stripped tinned, 26 AWG, UL2464 30-00061, shielded
10-00541	Cable, 1830 mm, 5P 90° mini-DIN male 50-00158, to stripped tinned, 26 AWG, UL2464 30-00062, shielded
10-00542	Cable, 1830 mm, 6P 90° mini-DIN male 50-00159, to stripped tinned, 26 AWG, UL2464 30-00063, shielded
10-00543	Cable, 1830 mm, 7P 90° mini-DIN male 50-00160, to stripped tinned, 26 AWG, UL2464 30-00064, shielded
10-00544	Cable, 1830 mm, 8P 90° mini-DIN male 50-00161, to stripped tinned, 26 AWG, UL2464 30-00065, shielded
10-00545	Cable, 1830 mm, 9P 90° mini-DIN male 50-00162, to stripped tinned, 26 AWG, UL2464 30-00058, shielded
10-00546	Cable, 1830 mm, 3P 90° mini-DIN female 50-00163, to stripped tinned, 26 AWG, UL2464 30-00060, shield
10-00547	Cable, 1830 mm, 4P 90° mini-DIN female 50-00164, to stripped tinned, 26 AWG, UL2464 30-00061, shield
10-00548	Cable, 1830 mm, 5P 90° mini-DIN female 50-00165, to stripped tinned, 26 AWG, UL2464 30-00062, shield
10-00549	Cable, 1830 mm, 6P 90° mini-DIN female 50-00166, to stripped tinned, 26 AWG, UL2464 30-00063, shield
10-00550	Cable, 1830 mm, 7P 90° mini-DIN female 50-00167, to stripped tinned, 26 AWG, UL2464 30-00064, shield
10-00551	Cable, 1830 mm, 8P 90° mini-DIN female 50-00168, to stripped tinned, 26 AWG, UL2464 30-00065, shield

Purchase orders for these products will be considered non-cancelable, non-returnable (NCNR). Products purchased during this end-of-life transition period will be fully covered by Tensility's standard product warranty. Failure analysis will be limited to verification of failure and remedies will be limited to credit of the product purchase price.

Please direct all questions regarding this EOL to:

info@tensility.com
541-323-3228