

16379.2 GSM-ANTENNA-90°



GSM omni-directional antenna, 90° with SMA round connector

Business data

Article number	<u>16379.2</u>
Article name	GSM-ANTENNA-90°
GTIN (EAN)	4044211207793
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	6 g
Weight per piece (including packaging)	10 g
Unit of weight	G
Customs number	85291069
Country of origin	EU
Product description	GSM antenna

16379.2 GSM-ANTENNA-90°

Technical data

Dimensions

Width	8 mm
Height	49.5 mm
Installation height	41 mm

Connection data

Plug-in connector	SMA-Male
Antennengewinn max.	1,0 dBi (824 – 960 MHz), 2,0 dBi (1710 – 1990 MHz), 2,5 dBi (1920 – 2170 MHz)
GSM frequency	800, 850, 900, 1900, 2100 MHz
Impedance	50 Ohm

Materials

Material	PC, PCT
Working temperature, min.	-40 °C
Working temperature, max.	75 °C

Further technical data

Mounting type	On module
Antenna shape	Stubby

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-01-07
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16368.2</u>	GSM-PRO2	4044211207731	1 ST



Compact reporting system for mobile networks, for monitoring analogue and digital values ??and remotely switching relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16369.2</u>	GSM-PRO2-GPS	4044211207748	1 ST



Compact signaling system for mobile networks to monitor analog and digital values ??as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16407.2</u>	GSM-PRO2E	4044211219017	1 ST



Compact reporting system for mobile networks to monitor analogue and digital values ??as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16408.2</u>	GSM-PRO2E-GPS	4044211219024	1 ST