

## 8-Port DisplayPort to HDMI over Cat6 Splitter/Extender, Transmitter for Video/Audio, PoC, 4K 60 Hz, 125 ft. (38 m), TAA

MODEL NUMBER: B127-008-D



Transmitter/splitter extends a 4K DisplayPort audio/video signal via Cat6 cable to 8 HDMI monitors or HDTVs up to 125 ft. away.

### Features

**Splitter Ideal for Digital Signage or Displaying Video in Schools or Trade Show Booths** This eight-port transmitter/splitter is recommended for video presentations in conference rooms, schools, trade shows, meeting facilities, houses of worship, retail settings and other digital signage applications where the source and display are farther apart than conventional A/V cables allow. The B127-008-D extends 4K video and stereo audio signals from a DisplayPort source device to eight HDMI-enabled projectors, monitors or televisions up to 125-ft. (38.1 m) away via user-supplied Cat6 cabling.

**Built-In PoC Technology Provides Power to Avoid Bulky External Power Bricks** Built-in Power over Cable (PoC) technology powers the connected B127-Series receivers over Cat6 cable. Green and orange LEDs will light up to indicate the unit is receiving power and a signal is being received. PoC lets you avoid the hassle of a bulky power brick and gives you the freedom to place the receivers away from an AC outlet.

**Transmits Crystal-Clear 4K Video with Multi-Channel Audio and 4:4:4 Color** The B127-008-D supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz with full, rich uncompressed DTS-HD, Dolby AC-3 and 8-channel LPCM digital audio. The transmitter also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

**Plug-and-Play Operation for Quick Setup and Immediate Use** The included transmitter works right out of the box with no software required. Mounting hardware is included for installing the unit on a wall, pole or 19-inch rack. Connect the transmitter to the source with a user-supplied DisplayPort cable (such as Tripp Lite's P580-Series). Then, connect the transmitter to a Tripp Lite B127-100-H, B127-200-H or B127-100-H-SR remote receiver using Cat6 Ethernet cable (such as Tripp Lite N202-Series cable). You can also connect an optional display to the local HDMI output to monitor the image transmitted to the receivers up to 125-ft. (38.1 m) away.

**TAA-Compliant for GSA Schedule Purchases** The B127-008-D is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

### Highlights

- Requires Tripp Lite B127-100-H, B127-200-H or B127-100-H-SR remote receiver
- Maintains UHD resolutions up to 3840 x 2160 @ 60 Hz (4:4:4) for crystal-clear 4K video
- Power over Cable (PoC) technology provides power to the receivers via Cat6 cable
- Transmitter's local HDMI port allows you to see the image being displayed 125-ft. (38.1 m) away
- Plug-and-play operation with no software required for easy, immediate installation

### Applications

- Connect a media server, Blu-ray player, cable/satellite box, Roku, gaming system or other home theater component to 8 large-screen 4K televisions or projectors
- Upgrade the video quality of your trade show presentation in a commercial or educational setting to 4K x 2K
- Set up digital signage with a single video signal being transmitted to 8 monitors, each displaying its maximum resolution

### System Requirements

- Source device with DisplayPort output (Blu-ray player, cable box, laptop)
- Tripp Lite B127-100-H, B127-200-H or B127-100-H-SR remote receivers

### Package Includes

- Transmitter unit
- External power supply with 4.5-ft. (1.37 m) cord (Input: 100-240V, 50/60 Hz, 1.5A; Output: 24V 2A)
- (4) International plug adapters (North America, Europe, U.K. and Australia)
- Mounting hardware
- Owner's manual



## Specifications

OVERVIEW	
UPC Code	037332254788
Product Type	Transceiver
Technology	DisplayPort; HDMI; Cat5/5e; Cat6; POC
VIDEO	
Max Supported Video Resolution	3840x2160 (4K @ 60Hz)
Max 1280 x 720 (720p) Range (ft)	200
Max 1920 x 1080 (1080p) Range (ft)	200
Max 1920 x 1200 Range (ft)	150
Max 2560 x 1600 Range (ft)	150
Max 3840 x 2160 (4K@30Hz) Range (ft)	150
Max 3840 x 2160 (4K@60Hz) Range (ft)	125
Transmitter Video Input	DisplayPort
Transmitter - Number of Video Outputs	8
Transmitter - Local Display Output	HDMI
Recommended Cabling	Solid Wire Cat6 Cables (Tripp Lite's N202-Series)
Max Supported Color Depth	24-bit True Color
HDR Support	No
3D Video Supported	Yes
Chroma Sub Sampling	4:4:4
Maximum Signal Range (ft)	125
Maximum Signal Range (m)	38
AUDIO	
Audio Input	Displayport
Audio Specification	7.1 Channel Surround Sound, DTS-HD and Dolby TrueHD
INPUT	
Bus Powered	No
POWER	
Power Source Type	AC Adapter



AC Plug Type	NEMA 1-15P; BS1363; CEE 7/16 Schuko; AS/NZS 3112
Power Source	Transmitter end only (Included)
Power Over Cable (PoC) Support	Yes
External Power Supply Input Specs (V / Hz / A)	100-240V / 50-60Hz / 1.5A
External Power Supply Output Specs (V / A)	24V/2A
External Power Supply Cord Length (ft.)	4.5
External Power Supply Cord Length (m.)	1.38
External Power Supply Certifications	CCC; CE; FCC; GS; PSE; TUV; UL; cUL
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	Tx: x1 Green (Power); x10 Orange (Local, 1-8 Output, Input); Tx RJ45 Port: x8 Green (Connected), x8 Orange (Activity)
<b>PHYSICAL</b>	
Color	Black
Material of Construction	Metal
Included Mounting Accessories	Wallmount
Number of Displays	8
Form Factor/Mounting Options	Box; Wall-mount
Rackmountable	Yes
Shipping Dimensions (hwd / cm)	5.51 x 35.20 x 16.41
Shipping Dimensions (hwd / in.)	2.17 x 13.86 x 6.46
Shipping Weight (kg)	0.65
Shipping Weight (lbs.)	1.43
Unit Dimensions (hwd / in.)	1.169 x 9.252 x 3.97
Unit Dimensions (hwd / mm)	29.7 x 235 x 100
Unit Packaging Type	Box
Unit Weight (kg)	0.65
Unit Weight (lbs.)	1.43
Housing	Metal
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32 TO 104° F (0 TO 40° C)
Storage Temperature Range	5 TO 122° F (-15 TO 50° C)
Relative Humidity	0% to 85% RH, Non-Condensing



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

<b>COMMUNICATIONS</b>	
Signal Range (ft.)	125
Signal Range (m)	38
Transmission Distance	3840 x 2160 (4K) @ 60 Hz, 4:4:4 = 125 ft (40 m); 3840 x 2160 (4K) @ 30Hz = 150 ft. (45 m); 1080p @ 60Hz = 200 ft (60 m)
EDID Compatible	Yes
IR Remote Extension Support	No
RS-232 Serial Extension Support	No
Consumer Electronics Control (CEC) Supported	Yes
USB Extension Support	No
<b>CONNECTIONS</b>	
Ports	8
Side A - Connector 1	HDMI (FEMALE)
Side A - Connector 2	DISPLAYPORT (FEMALE)
Side B - Connector 1	(8) RJ45 (FEMALE)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Displayport Specification	1.2a
HDCP Specification	2.2
Driver Required	No
Recommended Category Cable	Solid Wire Cat6 Cables (Tripp Lite's N202-Series)
10/100 Ethernet Extension Support	No
DIN Mountable	No
Integrated/Removable Cable	No
MST Support	No
Mounting Accessory Included	Yes
Multi-Resolution Support	Yes
Built-In Equalizer	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Certifications	Tested to CE, FCC, REACH, RoHS
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	1-year limited warranty



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:  
<https://www.tripplite.com/products/product-certification-agencies>