



CIRCUIT: SPDT

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
(DN)	DEF	(DN)
2-3	OPEN	2-1

() = MOMENTARY

CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERMINAL NUMBERS FOR REF ONLY
 4. RATING: 5 AMPS @ 120VAC OR 28VDC;
2 AMPS @ 250VAC
 5. ELECTRIC LIFE: 50,000 make-and-break cycles
at full load.
 6. INSULATION RESISTANCE: 1,000 Mega-ohm min.
 7. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
 8. OPERATING TEMP.: -30°C to 85°C



REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	10690	RELEASED FOR PRODUCTION	6/17/00	GLG

TITLE		SCALE		DATE	DR	DWG	REV
300 SP4 J6 VS2 Q E		2:1		6/17/00	GLG	T314022	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED