



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00006	Connector, 2.5xL21.6 mm, audio plug 4C with metal ring, brass nickel plated	2	
2	30-00413	Wire, 4C TC, 26 AWG, 30V, 80C, 3.7 mm, shielded, PVC, 89A	1	
3	24-00104	Overmold, PVC, black	2	



Wiring Diagram		
50-00006	wire color	50-00006
A	Red	A
B	Black	B
C	Green	C
D	Yellow	D

**Notes:**

Electical requirement: 2 A

Hi-Pot test: 300 Vac, 0.5 mA, 1 second

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	1/19/2009	Re-issued CUI spec as Tensility	<b>GL</b> 2016.02.22 10:44:42 -08'00"	RoHS compliant	
A1	5/11/2009	Added connector part number	<b>LA</b> <small>Digitally signed by LA DN: cn=LA, o=Tensility, ou=Engineering, email=LA002@Tensility.com, c=US Date: 2016.02.22 15:26:56 -08'00'</small>	Function test: no open, no short circuit, no intermittent	
A2	8/30/2011	Updated description and part number information	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:	
A3	5/6/2014	Updated description		Cable, 1830 mm, 4C 2.5mm 50-00006 plug with metal ring to same, 26 AWG, 30-00413	
Scale: 1:1				Size: A Part number: 053-0110R (CA-254CS-MM)	