



Note: '()' correspond to the letters used in the product bulletin

Click [here](#) for the 3D model.

### Dimensions

|           |                |
|-----------|----------------|
| Chip Size | 2824           |
| L         | 7.3mm +/-0.2mm |
| W         | 6mm +/-0.2mm   |
| T         | 3.5mm +/-0.2mm |
| F         | 0.5mm NOM      |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | T&R  |
| Packaging Quantity | 2300 |

### General Information

|                |                              |
|----------------|------------------------------|
| Series         | F161                         |
| Dielectric     | Metallized Polyester Stacked |
| Style          | SMD Chip                     |
| Features       | Automotive Grade             |
| RoHS           | Yes                          |
| Qualifications | AEC-Q200                     |
| AEC-Q200       | Yes                          |
| Shelf Life     | 104 Weeks                    |
| MSL            | 3                            |

### Specifications

|                       |                                  |
|-----------------------|----------------------------------|
| Capacitance           | 0.18 uF                          |
| Capacitance Tolerance | 5%                               |
| Voltage AC            | 63 VAC                           |
| Voltage DC            | 100 VDC                          |
| Temperature Range     | -55/+125°C                       |
| Rated Temperature     | 85°C                             |
| Dissipation Factor    | 0.8% 1kHz, 1.2% 10kHz, 3% 100kHz |
| Insulation Resistance | 1 GOhms                          |
| Max dV/dt             | 50 V/us                          |