

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/13/18	

D

C

B

A

RECOMMENDED PCB LAYOUT

SPECIFICATIONS:
 Material:
 Insulator: Hi-Temp Thermoplastic, rated UL 94V-0
 Insulator color: Black
 Contacts: Copper Alloy
 Shell: Stainless Steel
 Plating:
 Gold flash over Nickel underplate on contact area
 Electrical:
 Current rating: 1 A max
 Contact resistance: 30 mohms max.
 Insulation resistance: 100 Mohms min.
 Dielectric withstanding voltage: 100 VAC for 1 minute
 Temperature Rating:
 Temperature range: -30°C to +80°C
 Environmental:
 Lead free, RoHS compliant.

PACKAGED ON TAPE & REEL

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED INCHES HOLES .X ± .10 Ø.X ± .10 .XX ± .020 Ø.XX ± .015 .XXX ± .015 Ø.XXX ± .010		ADAM TECH INTERCONNECTS		909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
APPROVALS		DATE		TITLE	
DRAWN	HR	3/13/18		MICRO USB, TYPE B, SINGLE PORT, SOCKET, RIGHT ANGLE, SMT TYPE	
CHECKED	RC1	3/13/18		SIZE	PART NO.
APPROVED				X	MCR-B-S-RA-SMT-CS14-T/R
REF: S00097C		SCALE: NTS		REV. -	
				SHEET 1 OF 1	

6 5 4 3 2 1