


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00672	Connector, 3 pin M5 socket, 5xL14.7mm, gold plated, molding style, solder cup, IP67, shielded	2	
2	30-01638	Wire, 3C TS, 28 AWG, 150V, 70C, 2.8 mm, shielded, TPU, WBL	1	
3	24-00356	Overmold, M5 shielded, 180°, Ø7.5xL22 mm	2	TPU, black



Notes:
Functionally equivalent components may be substituted

IP67 waterproof rating when mated with corresponding (IP67) connector

Cable rated for 60 V, 1.0 A

Wiring Diagram		
50-00672	wire color	50-00672
1	red	1
3	white	3
4	black	4
Shell	shield	Shell

Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY
A	1/11/21	Initial release		RoHS compliant	
			Verified:	Function test: no open, no short circuit, no intermittent	tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 0.5 mm 3C 50-00672 M5 socket to same, 28 AWG, 30-01638 wire, IP67, shielded	Size: A Part number: 10-03868
					Scale: 1:1 Sheet 1 of 1

5

4

3

2

1