



ELESA original design CFH. / CFL.

Metric table

Dimensions in: millimeters - inches

| 1 l ₁ -0.5 | 2 l ₂ | 3 d ₁ | d ₂ | h ₁ | h ₂ | h ₃ | l ₃ | m ₁ ±0.25 | m ₂ ±0.25 | t | for screw DIN 7984 |
|---------------------------------|----------------------------|----------------------------|----------------|----------------|----------------|----------------|----------------|----------------------|----------------------|-------------|-----------------------|
| 70 2.76 | 50 1.97 | 6.5 0.26 | 6 0.24 | 19.5 0.77 | 10 0.39 | 21 0.83 | 24 0.94 | 45.5 1.79 | 30 1.18 | 6.5 0.26 | M 6 |
| 70 2.76 | 50 1.97 | 8.5 0.33 | 6 0.24 | 19.5 0.77 | 10 0.39 | 21 0.83 | 24 0.94 | 45.5 1.79 | 30 1.18 | 4.5 0.18 | M 8 |
| 80 3.15 | 102 4.02 | 6.5 0.26 | 5 0.20 | 20.5 0.81 | 13 0.51 | 26 1.02 | 35.5 1.40 | 49.5 1.95 | 72.5 2.85 | 6.5 0.26 | M 6 |
| 80 3.15 | 102 4.02 | 8.5 0.33 | 5 0.20 | 20.5 0.81 | 13 0.51 | 26 1.02 | 35.5 1.40 | 49.5 1.95 | 72.5 2.85 | 8 0.31 | M 8 |

Specification

- Plastic
Technopolymer (Polyamide PA)
- Temperature resistant up to 140 °F (80° C)
- Black, matte finish
- Hinge pin
Stainless steel
European standard 1.4305 (AISI 303)
- RoHS compliant

Information

- see also...
- List of Hinge Types

| | |
|--|---------------------------------------|
| <p>How to order</p> <p>1 2 3</p> <p>EN 157-70-50-8.5</p> | 1 Width l ₁ |
| | 2 Length l ₂ |
| | 3 Bore diameter d ₁ |