

Automation Products
UC20-WL2000-IOT**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image**

For modern IoT applications, automation technology needs to be increasingly more powerful and adaptable. u-mation offers a coordinated hardware portfolio designed for the future-proof preparation of your machines and systems. u-control 2000 is one of the most compact and state-of-the-art control systems on the market and is the centrepiece of our hardware portfolio. u-control 2000 forms the basis required for use of our engineering solutions u-create web, studio and IoT. The controllers modular design is based on the remote I/O system u-remote, and allows for needs-based expansion to include other components from the u-mation family.

General ordering data

Type	UC20-WL2000-IOT
Order No.	1334990000
Version	Controller, IP20, u-control 2000 web, IoT Controller, Web-based, incl. Engineering Tool u- create IoT (node red)
GTIN (EAN)	4050118138290
Qty.	1 pc(s).

Creation date July 1, 2020 6:44:26 PM CEST

Catalogue status 26.06.2020 / We reserve the right to make technical changes.

Data sheet

Automation Products UC20-WL2000-IOT

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	52	Width (inches)	2.047 inch
Height	120 mm	Height (inches)	4.724 inch
Depth	76 mm	Depth (inches)	2.992 inch
Mounting dimension - height	128 mm	Net weight	232 g

Temperatures

Operating temperature, max.	55 °C	Operating temperature, min.	-20 °C
-----------------------------	-------	-----------------------------	--------

Connection data

Type of connection	PUSH IN
--------------------	---------

General data

UL 94 flammability rating	V-0
---------------------------	-----

Power supply

Current consumption from I _{IN} (power segment of the field bus coupler), typ.	116 mA	Feed current for I _{IN} (input current path), max.	5 A
Feed current for I _{OUT} (output current path), max.	5 A	Feed current for the system, max.	4,000 mA
Supply voltage for outputs	24 V DC +20 %/ -15 %	Supply voltage system and inputs	24 V DC +20 %/ -15 %

System data

Configuration interface	Micro USB 2.0	Connection type	2 x RJ45 plug-in connectors
Interface	2x Ethernet TCP/IP, 1x Micro USB	Memory (Flash)	4 GB, 32 GB via microSD
Module type	Controller	Processor	Dual Core ARM Cortex A9, 624 MHz, 512 Mbyte RAM
Real-time clock	Battery buffered	Transmission speed backplane bus, max.	48 Mbit
max. number of modules	64		

Classifications

ETIM 6.0	EC001603	ETIM 7.0	EC001603
eClass 9.1	27-24-26-08	eClass 10.0	27-24-26-07

Approvals

Approvals



ROHS	Conform
------	---------

Automation Products
UC20-WL2000-IOT**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Technical data****Downloads**

Product Change Notification	Release-Notes - IoT
Software	Current Firmware file for UC20 IoT Archiv Firmware files UC20-WL2000-IOT
User Documentation	MANU UC20 XL2000 DE MANU UC20 XL2000 EN UC20-WL2000-IOT Supported modules list

**Automation Products
UC20-WL2000-IOT**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Connection diagram

