



Click [here](#) for the 3D model.

### Dimensions

|   |             |
|---|-------------|
| L | 130.5mm MIN |
| W | 56.5mm MIN  |
| H | 48.5mm MIN  |

### Packaging Specifications

|                    |       |
|--------------------|-------|
| Packaging          | Bulk  |
| Packaging Quantity | 1     |
| Component Weight   | 475 g |

### General Information

|                |                                     |
|----------------|-------------------------------------|
| Series         | FLLE2-R                             |
| Style          | Chassis Mount                       |
| Description    | Single Phase, Chassis Mount Filters |
| Features       | Single Phase                        |
| Phase          | Single-phase                        |
| RoHS           | Yes                                 |
| Qualifications | IEC/EN 60939, UL, CSA               |
| Terminal Type  | Threaded Studs M4                   |

### Specifications

|                            |               |
|----------------------------|---------------|
| Voltage AC                 | 300 VAC       |
| Voltage DC                 | 300 VDC       |
| Rated Frequency            | 50-60 Hz      |
| Rated Current              | 32 A          |
| Rated Temperature          | 40°C          |
| Temperature Range          | -25/+100°C    |
| Climate Category           | 25/100/21     |
| Leakage Current            | 0.79 mA (MAX) |
| Test Voltage DC (P/N to E) | 2250 VDC      |
| Test Voltage DC (P to N)   | 1300 VDC      |