

LINEAR TECHNOLOGY MATERIALS DECLARATION

ltc1667cg#trpbf

(Engineering Calculation)

SSOP

(printed on: 2020-07-11 19:15:25)

TOTAL MASS (g) : 0.232361

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.004306 | 1000000 | 18531.5136719 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.122431 | 975000 | 526900.125 | | |
| | | Iron (Fe) | 7439-89-6 | 0.003014 | 24000 | 12971.1982422 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000038 | 300 | 163.538650513 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000088 | 700 | 378.721130371 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.125571 | 1000000 | 540413.5 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.003749 | 1000000 | 16134.0869141 | | |
| | | External Plating Total: | | | | 0.003749 | 1000000 | 16134.0869141 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.001005 | 1000000 | 4325.16748047 | | |
| Internal Plating Total: | | | | 0.001005 | 1000000 | 4325.16748047 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.001172 | 750000 | 5043.87695312 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000391 | 250000 | 1682.72692871 | | |
| Die Attach Total: | | | | 0.001563 | 1000000 | 6726.60400391 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.009848 | 103000 | 42382.3359375 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.085571 | 895000 | 368267.5625 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000191 | 2000 | 821.997009277 | | |
| | | Encapsulation Total: | | | | 0.095610 | 1000000 | 411471.90625 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000557 | 1000000 | 2397.13256836 | | |
| | | | | | TOTAL MASS (g) : | 0.232361 | | |