ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00404	Connector, mono plug, 2.5xL19.6 mm, brass, nickel plated, white, molding style	1	
2	30-00178	Wire, 2C BC, 28 AWG, 300V, 80C, 3.8 mm, foil + shield, PVC, white	1	
3	24-00028	Overmold, PVC, white	1	white



Notes:
Cables individually tied and bundled in groups of 10

Functionally equivalent components may be substituted

Wiring Diagram	
50-00404	wire color
tip	red
sleeve	white

Revision:	Date:	Description:
A	4/14/2010	Initial release
A1	9/6/2011	Updated specification
A2	3/28/2012	Updated wire part number
A3	3/27/2014	Updated connector
A4	10/28/2016	Corrected overmold dimensions

Prepared: GL Digitally signed by GL Date: 2016.10.28 13:51:51 -07'00'

Verified: DN Digitally signed by DN Date: 2016.10.28 15:10:06 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Cable, 1830 mm, 2.5 mm 50-00404 slim mono plug to 5 mm tinned, 28 AWG, 30-00178, shielded, white

TENSILITY

tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A

Part number: 10-00334

Scale: 1:5

Sheet 1 of 1

5 4 3 2 1