




# Specialty Terminals

70F-110-20-PB, 70F-110-32-PB

Female Quick-Slide, Vinyl Insulated with Insulation Grip



## Data Sheet

3M™ Product Number	Wire Range (AWG)	Mates with Tab	L	Barrel I.D.	Maximum Insulation Diameter
		Width x Thickness			
70F-110-20-PB	26-22	.110 x 0.20	0.63	.040	.075
70F-110-32-PB	26-22	.110 x .032	0.63	.040	.075

### Specifications

Wire Size:	See Table Above
Barrel Seam:	Butted with Insulation Grip
Maximum Operating Temp:	221°F (105°C)
Maximum Current:	Same as Wire
Insulator Material:	Vinyl
Terminal Material:	Brass
Insulation Grip Material:	Copper
Plating:	Tin

### Installation Information

#### **⚠ WARNING**

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

For use on stranded copper wire only.

Strip away the end 3/16 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M Scotchlok Crimping Tool TH-450.



● Barrel Crimp (Electrical)

□ Insulation Crimp (Mechanical)

## Engineering Specification

Crimp-Type Female Quick-Slide connectors shall, electrically and mechanically, connect permanently to a prestripped end of a stranded copper wire, and have a tongue portion with fingers which grip a Male Disconnect in a separable, reusable manner, forming a Quick Connect Wiring Termination.

The connector line shall offer tongue variations (sized to grip male tabs 0.110" x 0.020" or 0.110" x 0.032") and barrel variations in construction, non- insulated, vinyl insulated with insulation grip, nylon fully insulated, etc.

The Vinyl Insulated Miniature 0.110" Female Disconnect with insulation grip, shall be tin plated 0.010" thick brass with a tongue for gripping a 0.110" male tab of either 0.020" or 0.032" thickness and with a barrel covered by a copper insulation grip, which is covered by a vinyl sleeve, color coded and sized for a specified (AWG) wire range (26-22).

3M and Scotchlok are trademarks of 3M Company.

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of five (5) years from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



### Electrical Markets Division

6801 River Place Blvd.  
Austin, TX 78726-9000  
800-245-3573  
Fax 800-245-0329  
[www.3M.com/electrical](http://www.3M.com/electrical)

Please recycle. Printed in USA.  
© 3M 2007. All rights reserved.  
78-8131-7368-5-A