## ATGBICS ST-ST OM3, Fibre Optic Cable, Multimode, Simplex, Aqua, 20m

**Brand :** ATGBICS **Product code:** CAB-OM3-ST-ST-20M-S

**Product name :** ST-ST OM3, ATGBICS Fibre Optic Cable,


Multimode, Simplex, Aqua, 20m

ATGBICS°

ST-ST OM3, ATGBICS Fibre Optic Cable, Multimode, Simplex, Aqua, 20m

ATGBICS ST-ST OM3, Fibre Optic Cable, Multimode, Simplex, Aqua, 20m:

This product is high quality Simplex ST-ST (male to male ) Fibre Patch Cable. Simplex Fibre is most often used for applications that only require one-way data transfer. The OM3 cable has a core size of 50 microns and the diameter of the outer cladding is 125 microns. Our OM3 fibre patch cables are designed to maintain a low attenuation loss and speed stability. Our products are rigorously tested and we proudly offer a compatibility guarantee and lifetime warranty.





Cable length * 20 m  Connector 1 * ST  Connector 2 * ST  Connector 1 gender * Male  Connector 2 gender * Male  Connector polish type  Cable type * OFNR  Fibre optic type * OM3  Product colour * Aqua colour  Full duplex  Core diameter  Cladding diameter  Fiber mode structure  Wavelengths supported  20 m  ST  ST  OM3  Aqua  Aqua  Core  Male  UPC  OFNR  OFNR  Fibre optic type *  OM3  Aqua colour  Full duplex  X  Core diameter  S0 µm  Cladding diameter  125 µm  Fiber mode structure  Multi-mode  Wavelengths supported	Ethernet interface type Insertion loss Return loss Jacket material *	10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit Ethernet 0.2 dB 50 dB Polyvinyl chloride (PVC) China
	Technical details  Sustainability certificates  Doesn't contain	RoHS Halogen
	Operational conditions Operating temperature (T-T) Storage temperature (T-T)	-40 - 70 °C -40 - 70 °C
	Weight & dimensions Cable diameter Packaging data	2 mm
	ST ST Male Male UPC OFNR OM3 Aqua colour  X 50 µm 125 µm Multi-mode	ST ST Insertion loss Male Male UPC OFNR Technical details OM3 Aqua colour Doesn't contain  Coperational conditions Operating temperature (T-T) Multi-mode 850,1300 nm Ethernet interface type Insertion loss Return loss Jacket material * Country of origin Technical details Sustainability certificates Doesn't contain  Operational conditions Storage temperature (T-T) Weight & dimensions Cable diameter



5056468742353

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.