


Cable - CAB-DSUB25M/OE/18/S/ 3M - 2909760

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules); connection 2: D-SUB pin strip (1x 25-position); cable length: 3 m

Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Individual wires fitted with ferrules
- Screw connection: 2 UNC 4-40 screws
- Open end at one end
- D-SUB socket or pin strip at one end
- 1:1 connection



Key Commercial Data

| | |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 055626 682754 |
| GTIN | 4055626682754 |

Technical data

Dimensions

| | |
|--------|-----|
| Length | 3 m |
|--------|-----|

Ambient conditions

| | |
|-----------------------------------------|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

General

| | |
|-----------------------------------------|----------|
| Max. permissible operating voltage | 125 V AC |
| | 125 V DC |
| Max. current carrying capacity per path | 2 A |

Cable - CAB-DSUB25M/OE/18/S/ 3M - 2909760

Technical data

Cable

| | |
|----------------------------------|--------------------------------|
| Length of cable | 3 m |
| Type of cable | Assembled shielded round cable |
| Single wire, cross section | 0.75 mm ² |
| Single wire, cross section [AWG] | 18 |
| External cable diameter | 14.3 mm |
| Shielding | yes |
| Halogen-free cable | No |

Connection data

| | |
|-----------------------|-----------------|
| Connection name | Field level |
| Connection method | D-SUB pin strip |
| Number of connections | 1 |
| Number of positions | 25 |

Connection data 2

| | |
|---------------------|-----------------------------------------------|
| Connection name | Controller level |
| Connection method | Single wires |
| Number of positions | 25 |
| Note | The wires are marked and fitted with ferrules |

Supported controller

| | |
|------------|-----------|
| Controller | universal |
|------------|-----------|

Color code

| | |
|---------------------------------------------------|-----------------------------|
| Connector 1 = connector 2 (optional) = wire color | D-SUB25 (1) = black |
| | D-SUB25 (2) = red |
| | D-SUB25 (3) = white |
| | D-SUB25 (4) = green |
| | D-SUB25 (5) = orange |
| | D-SUB25 (6) = blue |
| | D-SUB25 (7) = brown |
| | D-SUB25 (8) = yellow |
| | D-SUB25 (9) = violet |
| | D-SUB25 (10) = slate |
| | D-SUB25 (11) = pink |
| | D-SUB25 (12) = tan |
| | D-SUB25 (13) = red-green |
| | D-SUB25 (14) = red-yellow |
| | D-SUB25 (15) = red-black |
| | D-SUB25 (16) = white-black |
| | D-SUB25 (17) = white-red |
| | D-SUB25 (18) = white-green |
| | D-SUB25 (19) = white-yellow |

Cable - CAB-DSUB25M/OE/18/S/ 3M - 2909760

Technical data

Color code

| | |
|--|--------------------------------|
| | D-SUB25 (20) = white-blue |
| | D-SUB25 (21) = white-brown |
| | D-SUB25 (22) = white-orange |
| | D-SUB25 (23) = white-slate |
| | D-SUB25 (24) = white-violet |
| | D-SUB25 (25) = white-black-red |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27242220 |
| eCl@ss 11.0 | 27242220 |
| eCl@ss 9.0 | 27242220 |

ETIM

| | |
|----------|----------|
| ETIM 7.0 | EC000237 |
|----------|----------|

Accessories

Accessories

Marker carrier cable

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable binders, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

Phoenix Contact 2021 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>