

Specification Sheet

Part Number: 126-00080

Design helps silence and stabilize the tie in high-vibration applications. Arrowhead-style mount provides low insertion and high extraction force. Anti-rotational oval fastener forces bundle to travel in intended direction. Rubber seal restricts water and debris from passing through mounting hole.



Push Mount Tie with Seal, 6.2" Long, Mounting Hole Diameter 0.24"-0.48", PA66HS, Black, 500/pkg

Article Number 126-00080

Type T60SOSSFT62x122-E-MD

Color Black (BK)

Quantity Per bag

Product Description Push Mount Ties with Seal for Oval Holes provide a one-piece bundling and mounting solution. The oval arrowhead fastener won't rotate once inserted into a panel hole, ensuring proper routing of wires and hoses. The welded rubber seal protects against the ingress of water and debris.

Short Description Push Mount Tie with Seal, 6.2" Long, Mounting Hole Diameter 0.24"-0.48", PA66HS, Black, 500/pkg

Global Part Name

T60SOSSFT62x122-E-MD-PA66HS-BK

Minimum Tensile Strength (Imperial) 67.0

Minimum Tensile Strength (Metric) 300

Length L (Imperial) 6.2

Length L (Metric) 157.5

Fixation Method Arrowhead for oval holes

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.22

Width W (Metric) 5.5

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 1.18

Bundle Diameter Max (Metric) 30.0

| | |
|--|--|
| Thickness T (Metric) | 1.35 |
| Panel Thickness Min (Imperial) | 0.023 |
| Panel Thickness Max (Imperial) | 0.079 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 2.0 |
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.48 |
| Mounting Hole Diameter D (Metric) | 6.2 x 12.2 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.48 |
| Mounting Hole Diameter D Max (Metric) | 12.2 |
| Disc Diameter (Metric) | 16.0 x 22.0 |
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988