



**TECHNICAL**

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	240VAC
RATED CURRENT:	UP TO 20 AMPS
RESET TYPE:	MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	4-6 mA
OVERLOAD CURRENT:	120 AMP
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3000 OPERATIONS
ENCLOSURE:	NEMA 3R

MATERIAL NO.	PART NO.	OUTPUT CORD LENGTH	VOLTAGE
1301530203	30-0905	9.00 IN. ± 0.5"	240VAC
1301530204	30-0906	5.0 FT. ± 1.0"	240VAC
1301530205	30-0907	24.0 FT. +2.0"/-0.0"	240VAC

FUNCTIONAL SYMBOLS $\nabla_A = 0$ $\nabla_C = 0$ $\nabla_P = 0$	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: UPDATED GFCI BODY.					
	DIMENSION UNITS	SCALE	 IN-LINE GFCI 20A, 240V FLYING LEADS					
	INCH	NTS						
	GENERAL TOLERANCES (UNLESS SPECIFIED)							
ANGULAR TOL	± °							
DIVISIONAL SYMBOLS 4 PLACES ± 3 PLACES ± 2 PLACES ± 1 PLACE ± 0 PLACES ±	EC NO: 730358		2022/10/19					
	DRWN: PPURSUTANDEL		2023/02/16					
	CHK'D: DNGUYEN2		2023/02/21					
	APPR: HKNEELAND		2023/02/21					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
			C-SIZE	130153	1301530203	PSD	000	B
					SEE TABLE	GENERAL MARKET		1 OF 1