

LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Stainless Steel
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +200°C
- Salt Spray : 500 hours


| Connector dimension |                 |
|---------------------|-----------------|
| Dim                 | Nominal         |
| A                   | 30.2±0.3        |
| B                   | 16.53+0.1/-0.15 |
| R                   | 32.5Max         |
| S                   | 27±0.4          |
| W                   | 2.2+0.9/-0.1    |
| VV THREAD           | M12x1-6g        |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D709S35AN**

|                |   |   |                               |
|----------------|---|---|-------------------------------|
| A              | 03-11-2016                                  | First Release   |                               |
| ISS            | DATE  | Latest modification - by  | MOD N°                        |
| Designed By:   |   | Date:   | <b>CUSTOMER DRAWING</b>       |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |   |                               |
| SCALE          |   | General linear Tolerances: ±--  | NPRDS / PROJECT<br><b>859</b> |
| NA             |   | This document is the property of SOURIAU it must not be reproduced or communicated without permission |                               |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |   |                               |
| FORMAT         | <b>SOURIAU DRG N° 8D709S35AN-C</b>          |   | SHEET<br>1/2                  |



Contact Layout



| Contacts<br>(Insert arrangement 9-35) |                  |             |
|---------------------------------------|------------------|-------------|
| Contact position ID                   | Contact location |             |
|                                       | X-axis (mm)      | Y-axis (mm) |
| 1                                     | +045 (1.14)      | +078 (1.98) |
| 2                                     | +078 (1.98)      | -045 (1.14) |
| 3                                     | +000 (0.00)      | -090 (2.29) |
| 4                                     | -078 (1.98)      | -045 (1.14) |
| 5                                     | -045 (1.14)      | +078 (1.98) |
| 6                                     | +000 (0.00)      | +000 (0.00) |

(Applicable to MIL-DTL-38999 and SAE-AS29600)

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 9          | -35             | 6                  | 22D           | M              | All              | MS27525-35 |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



| Dim | Nominal      |
|-----|--------------|
| B   | 16.7±0.1     |
| ØC  | 17.6+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D709S35AN

|                |   |                            |   |
|----------------|---|----------------------------|---|
| A              | 03-11-2016                                  | First Release              |   |
| ISS            | DATE  | Latest modification - by   | MOD N°  |
| Designed By:   |   | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |                            |   |
| SCALE          |   | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |   | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D709S35AN-C</b>          |                            | SHEET 2/2   |