т Q т т		>		
	LAYOUT SHOWN AS EXAMPLE			
Keying Shown as example				
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal				
ØS 32.5 Max				
-Shell Plating : Nickel Z 31 Max VV THREAD M22x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with			
-Insulator : Thermoplastic	the Specifications issued by either of the Parties or by a third party			
-Contacts : Copper Alloy	(professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer	Country Jurisdiction & Control List			
-Contact Plating : Gold over copper Alloy 0.8µm minimum	FR Not Listed			
-Durability : 500 Mating cycles	PN: 8D515F05BC			
-Delivered with Souriau contacts and Accessories				
-Temperature Range -65°C to +200°C	A 19-10-2016 First Release			
-Salt Spray : 48 hours -Mass : 31.38 g ± 10%	ISS DATE Latest modification - by	MOD N°		
141035 . 51.50 g ± 10/0	Designed By: Date: CUSTOMER DRAWING			
	TITLE Aluminium Plug 8D series	TITLE Aluminium Plug 8D series		
	SCALE General linear NPRDS / PROJECT			
BASIC SERIES: 8D 5 - 15 F 05 B C	Tolerances: 859			
SHELL TYPE : Plug with RFI Shielding	NA ± 059 This document is the particular This document is the particular	property of		
CONTACT TYPE : Standard Crimp Contact ORIEN				
SHELL SIZE : 15 CONTACT TYPE : SOCKET(50				
PLATING : F = Nickel CONTACT LAYO		SHEET		
	A3 8D515F05BC-C	1/2		

	Ŧ	۵	г	m	D	0
4	د 	Contact Layout $ \begin{array}{c} & & \\$				
		Location X-axis Y-axis (mm) (mm) +.000 (0.00) +.100 (2.54) +.174 (4.42) +.024 (0.61) +.094 (2.39) 148 (3.76) 094 (2.39) 148 (3.76)				
ယ						
2						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda Count FR
					A 19-10-202	PN: 8D515
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
_					SCALE NA	General linear Tolerances: ±
					SOURIAU	
					FORMAT A3	SOURIAU 8D515F
	Н	G	F	E	D	C

