



Nanonics Standard Catalog Part Number Cross-Reference

Revision 1

TE P/N	TE CD	Nanonics P/N	Part Description
1589452-1	1589452	USS004L2	Unshrouded, 1 row, strip, 4 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe.
1589452-2	1589452	USS004L2T	Unshrouded, 1 row, strip, 4 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe, accepts guide post in position 1.
1589452-3	1589452	USS009L2	Unshrouded, 1 row, strip, 9 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe.
1589452-4	1589452	USS009L2T	Unshrouded, 1 row, strip, 9 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe, accepts guide post in position 1.
1589452-5	1589452	USS009L2U	Unshrouded, 1 row, strip, 9 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe, accepts guide post in position 2.
1589452-6	1589452	USS009L2V	Unshrouded, 1 row, strip, 9 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe, accepts guide post in position 3.
1589452-7	1589452	USS015L2	Unshrouded, 1 row, strip, 15 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe.
1589452-8	1589452	USS015L2T	Unshrouded, 1 row, strip, 15 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe, accepts guide post in position 1.
1589452-9	1589452	USS015L2V	Unshrouded, 1 row, strip, 15 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe, accepts guide post in position 3.
1-1589452-0	1589452	USS025L2	Unshrouded, 1 row, strip, 25 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe.
1-1589452-1	1589452	USS037L2	Unshrouded, 1 row, strip, 37 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe.
1-1589452-2	1589452	USS037L2T	Unshrouded, 1 row, strip, 37 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe, accepts guide post in position 1.
1-1589452-3	1589452	USS051L2	Unshrouded, 1 row, strip, 51 position, receptacle, horizontal mount, surface termination, .020 foot, tin/lead leadframe.