



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Stainless Steel
- Shell Plating : Passivated
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +200°C
- Salt Spray : 500 hours

| Connector dimension |          |
|---------------------|----------|
| Dim                 | Nominal  |
| ØS                  | 41.7 Max |
| Z                   | 31 Max   |
| VV THREAD           | M31x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D521K72PAL**

|   |                                     |                                |                               |
|---|-------------------------------------|--------------------------------|-------------------------------|
| A   | 07-10-2016                          | First Release                  |                               |
| ISS   | DATE                                | Latest modification - by       | MOD N°                        |
| Designed By:  |                                     | Date:                          | <b>CUSTOMER DRAWING</b>       |
| <b>TITLE</b>  |                                     | Stainless Steel Plug 8D series |                               |
| SCALE   | NA                                  | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b> |
| <b>SOURIAU</b>  |                                     | WWW.SOURIAU.COM                |                               |
| This document is the property of SOURIAU it must not be reproduced or communicated without permission |                                     |                                |                               |
| FORMAT  | <b>SOURIAU DRG N° 8D521K72PAL-C</b> |                                | SHEET<br>1/2                  |

|                |                         |   |   |    |   |    |   |   |   |                                 |
|----------------|-------------------------|---|---|----|---|----|---|---|---|---------------------------------|
| BASIC SERIES:  | 8D                      | 5 | - | 21 | K | 72 | P | A | L | Delivered W/O Contacts          |
| SHELL TYPE :   | Plug with RFI Shielding |   |   |    |   |    |   |   |   | ORIENTATION : A                 |
| CONTACT TYPE : | Standard Crimp Contact  |   |   |    |   |    |   |   |   | CONTACT TYPE : PIN(500 Matings) |
| SHELL SIZE :   | 21                      |   |   |    |   |    |   |   |   | CONTACT LAYOUT : 21-72          |
| PLATING :      | K = Passivated          |   |   |    |   |    |   |   |   |                                 |

Contact Layout

72



2#4 Power  
6#16

| 21-72 |       |       |
|-------|-------|-------|
| Ctc   | X     | Y     |
| A     | 0     | 6.19  |
| B     | 8.5   | 4.3   |
| C     | 6.25  | 0     |
| D     | 8.5   | -4.3  |
| E     | 0     | -6.19 |
| F     | -8.5  | -4.3  |
| G     | -6.25 | 0     |
| H     | -8.5  | 4.3   |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D521K72PAL

|                |                                       |                            |   |
|----------------|---------------------------------------|----------------------------|---|
| A              | 07-10-2016                            | First Release              |   |
| ISS            | DATE                                  | Latest modification - by   | MOD N°  |
| Designed By:   |                                       | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Plug 8D series</b> |                            |   |
| SCALE          |                                       | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                       | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D521K72PAL-C</b>   |                            | SHEET<br>2/2  |