

## Ha-Vis EtherRail 4xAWG22/7 bk CAT5 10m




Image is for illustration purposes only. Please refer to product description.

Part number	09 45 600 0168
Specification	Ha-Vis EtherRail 4xAWG22/7 bk CAT5 10m
HARTING eCatalogue	<a href="https://b2b.harting.com/09456000168">https://b2b.harting.com/09456000168</a>

### Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Copper cable (round)
Description of the cable	for railway applications

### Version

Cable length	10 m
Number of cores	4
Core structure	4x AWG 22/7

### Technical characteristics

Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 ... +85 °C unmoved -25 ... +70 °C moved
Cable diameter	6.4 ... 6.8 mm
Minimum bending radius	6x Cable diameter
Test voltage $U_{r.m.s.}$	1 kV Wire / wire / shielding
Coupling attenuation @ 20 °C / 100 MHz	8 mΩ/m
Conductor resistance @ 20 °C	≤54.4 Ω/km
Insulation resistance @ 20 °C	≥5,000 MΩ x km
Signal run time @ 20 °C	≤4.4 ns/m



Pushing Performance

## Technical characteristics

Impedance @ 100 MHz	100 Ω ±5 %
---------------------	------------

## Material properties

Material (cable)	Polyolefin copolymer electron beam crosslinked Comp 752
Colour (cable)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide

## Specifications and approvals

Specifications	EN 45545-2 (HL 1-3) fire protection in railway vehicles
	EN 50264-1 fire protection in railway vehicles
	EN 50306-1 fire protection in railway vehicles
	NFPA 130 fire protection in railway vehicles
	UN/ECE-R 118 fire protection for rolling stock
	EN 50306-4 Resistance to ozone
	EN 60811-504 High low temperature resistance
	EN 60811-404 High oil resistance
	EN 60811-404 High fuel resistance
	EN 60811-404 Alkali resistance
	EN 60811-404 Acid resistance
	DIN 51900 Low fire load
	EN 50618 UV resistant

## Commercial data

Packaging size	1
Net weight	686 g
Net weight	61 g/m
Country of origin	Switzerland
European customs tariff number	85444290
eCl@ss	27061801 Data and communication cable (copper)