



Keying Shown as example

CHARACTERISTICS

ω

 \sim

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Composite				
-Shell Plating	: Without Plating				
-Insulator	: Thermoplastic				
-Contacts	: Copper Alloy				
-Seals & Grommet	: Silicon Elastomer				
-Contact Plating	: Gold over copper Alloy $0.8 \mu m$ minimu				
-Durability	: 500 Mating cycles				
-Delivered with Souriau contacts and Accessories					

Thread

 \geq

Connector dimension					
Dim	Nominal				
Р	3.25±0.2				
РР	4.93±0.2				
R1	31.75				
R2	29.36				
S	39.7±0.3				
V	20.07+0/-1.25				
W	2.1/3.2				
Z	31.5 Max				
VV THREAD	M31x1-6g				

			v	20.07+0/-1.25		L			
-Seals & Grommet	: Silicon Elastomer		W	2.1/3.2]				Count
-Contact Plating	: Gold over copper Alloy 0.8µm minimum		Z	31.5 Max					FR
-Durability	: 500 Mating cycles		VV THREAD	M31x1-6g	J				
-Delivered with Souria	au contacts and Accessories							Р	N: 8D021
-Temperature Range	-65°C to +175°C							5' · D ·	
-Salt Spray	: 2000 hours					A 30-09	9-2016	First Release	
						ISS D/	ATE	Latest modificatio	n - by
					De	esigned By:	I	Date:	
						TITLI	E		Composite
BASIC SERIES:	8D 0 - 21 X	77 S N	1			SCALE			General linear
SHELL TYPE : Square						NA	-	$\exists \Theta$	Tolerances: ±
CONTACT TYPE : Sta	andard Crimp Contact			ORIEN	TATION : N	SOUR	IAU	WWW.	SOURIAU.C
SHELL SIZE : 21			CONTAG	CT TYPE : SOCKET(50					
PLATING : X =	Without Plating			CONTACT LAYO	DUT : 21-77	FORMAT			SOURIAU
						A3			8D021X
Н	G	F		E	/ D			С	

O		Ξ		Þ			
					4		
LAY	YOUT SHOWN AS EXA	MPLE			3		
SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) $\frac{Country \qquad Jurisdiction \& Control List \\\hline FR \qquad Not Listed}$ PN: 8D021X77SN							
First Release Latest modificatio	n - by			MOD N°			
Date: CUSTOMER DRAWING Composite Receptacle 8D series							
	General linear Tolerances: ±)M	NPRDS / PROJECT 859 This document is the SOURIAU it must not be repro		1		
Communicated without permission SOURIAU DRG N° SHEET							
С	8D021X7	7SN-C		1/2 A	J		
~	•	_		-			

					1	
-	Ŧ	۵	нт —	m		0
		Contact Layout				Panel Cutout
4		77			τ <u>γ</u>	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
		17#22D 2#8 Triax				
		21-77	Г		¥	
	Ctc	X Y]			
	A	1.96 8.38				
	В	5.46 7.67	4			Dim
	c	8.51 5.79	-			ØA
ယ	D	10.46 2.82 10.46 -2.82	-			ØAA R1
	F	8.51 -5.79	-			ØT
	G	5.46 -7.67	1			
	н	1.96 -8.38				
	J	0 -5.41	_			
	ĸ	-1.96 -8.38	-			SOURIAU shall not be liable for any
	L	-5.46 -7.67 -8.51 -5.79				due to a use of the Products whi
	N	-10.46 -2.82	-			the Specifications issued by either of (professional recommendati
	P	-10.46 2.82	1			
N	R	-8.51 5.79				Country FR
	S	-5.46 7.67	_			
	Т	-1.96 8.38	4			PN: 8D021X
	V	-4.57 0 4.57 0	-			
	v	4.57 0			A 30-09-20	016 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Composite
<u> </u>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D021X7
L	Н	G	F	E	D	С
					V	

