



650V/ 4A Silicon Carbide Power Schottky Barrier Diode

Features

- Zero reverse recovery current
- Zero forward recovery voltage
- Temperature independent switching behavior
- High temperature operation
- High frequency operation


Benefits

- Unipolar rectifier
- Substantially reduced switching losses
- No thermal run-away with parallel devices
- Reduced heat sink requirements

Applications

- SMPS, e.g., CCM PFC;
- Motor drives, Solar application, UPS, Wind turbine, Rail traction, EV/HEV

| Key Characteristics | | |
|-----------------------------------|-----|----|
| V_{RRM} | 650 | V |
| $I_F, T_c \leq 158^\circ\text{C}$ | 4 | A |
| Q_C | 11 | nC |



| Part No. | Package Type | Marking |
|----------|--------------|----------|
| G5S6504Z | DFN5*6 | G5S6504Z |

Maximum Ratings



| Parameter | Symbol | Test Condition | Value | Unit |
|---|-----------|---|--------------------|------|
| Repetitive Peak Reverse Voltage | V_{RRM} | | 650 | V |
| Surge Peak Reverse Voltage | V_{RSM} | | 650 | V |
| DC Blocking Voltage | V_{DC} | | 650 | V |
| Continuous Forward Current | I_F | $T_C=25^{\circ}C$ $T_C=125^{\circ}C$ $T_C=158^{\circ}C$ | 15.45 8.45 4 | A |
| Repetitive Peak Forward Surge Current | I_{FRM} | $T_C=25^{\circ}C$, $t_p=10ms$, Half Sine Wave, $D=0.3$ | 20 | A |
| Non-repetitive Peak Forward Surge Current | I_{FSM} | $T_C=25^{\circ}C$, $t_p=10ms$, Half Sine Wave | 35 | A |
| Power Dissipation | P_{TOT} | $T_C=25^{\circ}C$ | 84 | W |
| | | $T_C=110^{\circ}C$ | 37 | W |
| Operating Junction | T_j | | -55°C to 175°C | °C |
| Storage Temperature | T_{stg} | | -55°C to 175°C | °C |

Thermal Characteristics


| Parameter | Symbol | Test Condition | Value | Unit |
|--|------------|----------------|-------|------|
| | | | Typ. | |
| Thermal resistance from junction to case | R_{thJC} | | 1.78 | °C/W |

Electrical Characteristics


| Parameter | Symbol | Test Conditions | Numerical | | Unit |
|-------------------------|--------|--|-----------|------|---------|
| | | | Typ. | Max. | |
| Forward Voltage | V_F | $I_F=4A, T_j=25^\circ C$ | 1.4 | 1.6 | V |
| | | $I_F=4A, T_j=175^\circ C$ | 1.9 | 2.5 | |
| Reverse Current | I_R | $V_R=650V, T_j=25^\circ C$ | 0.07 | 50 | μA |
| | | $V_R=650V, T_j=175^\circ C$ | 0.65 | 100 | |
| Total Capacitive Charge | Q_C | $V_R=400V, T_j=150^\circ C$ $Q_C = \int_0^{V_R} C(V)dV$ | 11 | - | nC |
| Total Capacitance | C | $V_R=0V, T_j=25^\circ C, f=1MHz$ | 181 | 220 | pF |
| | | $V_R=200V, T_j=25^\circ C, f=1MHz$ | 22.5 | 25 | |
| | | $V_R=400V, T_j=25^\circ C, f=1MHz$ | 20.5 | 21 | |

Performance Graphs1) Forward IV characteristics as a function of T_j :2) Reverse IV characteristics as a function of T_j :


3) Current Derating:



4) Capacitance vs. reverse voltage:



Package DFN5*6



单位：mm

| DIM. | MILLIMETERS | | |
|------|-------------|------|------|
| | MIN. | NOM. | MAX. |
| A | 0.90 | 1.00 | 1.10 |
| A1 | 0 | — | 0.05 |
| b | 0.33 | 0.41 | 0.51 |
| c | 0.20 | 0.25 | 0.30 |
| D1 | 4.80 | 4.90 | 5.00 |
| D2 | 3.61 | 3.81 | 3.96 |
| E | 5.90 | 6.00 | 6.10 |
| E1 | 5.70 | 5.75 | 5.80 |
| E2 | 2.66 | 2.76 | 2.86 |
| e | 1.27 BSC | | |
| H | 0.41 | 0.51 | 0.61 |
| K | 2.00 | 2.10 | 2.20 |
| L | 0.53 | 0.63 | 0.73 |
| L1 | 0.06 | 0.13 | 0.20 |
| L3 | 0.15 | 0.25 | 0.35 |
| Q | 4.12 | 4.22 | 4.32 |
| α | 0° | - | 12° |

Note:

1. All Dimension Are In mm.
2. Package Body Sizes Exclude Mold Flash, Protrusion Or Gate Burrs.
Mold Flash, Protrusion Or Gate Burrs Shall Not Exceed 0.10 mm Per Side.
3. Package Body Sizes Determined At The Outermost Extremes Of The Plastic Body Exclusive Of Mold Flash, Tie Bar , Tie Bar Burrs, Gate Burrs And Interlead Flash, But Including Any Mismatch Between The Top And Bottom Of The Plastic Body.
4. The Package Top May Be Smaller Than The Package Bottom.

Note: The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC(RoHS2). RoHS Certification and other certifications can be obtained from GPT sales representatives or GPT website: <http://globalpowertech.cn/English/index.asp>

GPT's Alibaba Online Store is available now! You can place order with one click and get direct delivery from manufacturer in short time. For more info about products and price, please reach us at:

<https://globalpowertech.en.alibaba.com/>

More product datasheets and company information can be found in:

<http://globalpowertech.cn/English/index.asp>

