



Technical Datasheet

1 Mil Kapton Tape RoHS Compliant KPT Series

Kapton Tape is made from DuPont Kapton® Polyimide film with silicon adhesive. It has been used in applications at temperatures as low as -73°C (-99°F) and as high as 260°C (500°F).

Features:

- Thin and conformable enabling masking of uneven surfaces
- Wide operating temperature range up to 500°F
- Removes cleanly without adhesive residue after exposure to heat
- High performance silicone adhesive
- High strength backing provides superior resistance to puncture and tear
- Resistance to chemical attack

APPLICATIONS: 3D Printing, Aerospace Assembly, Automotive Facilities, Electronic Assembly, Fiber Optics Manufacturing, and Solar Panels.

TYPICAL PHYSICAL PROPERTIES ⁽¹⁾

Color	Amber
Adhesion Type	Silicone
Film Thickness	1 Mil
Adhesive Thickness	1.5 Mil
Total Thickness	2.5 Mil
Tensile Strength	30 lbs./in.
Elongation	40 %
Dielectric Strength	7,000 volts
Operating Temperature	-73°C (-99°F) to 260°C (500°F)
Resistance to acids, oils, solvents	Excellent
Length	36 Yards

Kapton® is a trademark of Dupont

⁽¹⁾ Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.

Bertech® makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech® assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.