



SS Stainless Steel

**Metric table**

Dimensions in: millimeters - inches

1 d <sub>1</sub> Thread	2 Length l						d <sub>2</sub>	k
	6	8	10	16	20	-		
M 3	.24	.31	.39	.63	.79	-	.47	2.5 .10
M 4	.31	.39	.47	.63	.79	25 .98	.63	3.5 .14
M 5	.39	.47	.63	.79	.98	30 1.18	.79	4 .16
M 6	.47	.63	.79	.98	1.18	40 1.57	.94	5 .20
M 8	.63	.79	.98	1.18	1.38	40 1.57	1.18	6 .24
M 10	.79	.98	1.18	1.38	1.57	-	1.42	8 .31

**Specification**

- Steel —
  - Tensile strength class 5
  - Blackened finish
  - Visible face fine turned
- Stainless steel **NI**
  - European Standard No. 1.4305 (AISI 303)
  - Matte shot-blasted finish
- RoHS compliant

**Information**

- DIN 653 flat knurled thumb screws are machined from solid bar.
- see also...
- Flat Knurled Thumb Screws GN 653.10 (Steel, with Brass / Plastic Tip)
  - Flat Knurled Thumb Screws GN 653.2 (with Recessed Stud for Loss Protection)
  - Knurled Thumb Screws DIN 464

How to order (Steel) 1 2 <b>DIN 653-M8-35</b>	1 Thread d <sub>1</sub>
	2 Length l

How to order (Stainless steel) 1 2 3 <b>DIN 653-M5-20-NI</b>	1 Thread d <sub>1</sub>
	2 Length l
	3 Material