



**TECHNICAL LISTED:**

RATED SUPPLY VOLTAGE:	120VAC	UL & CSA
RATED CURRENT:	UP TO 15 AMPS	
RESET TYPE:	MANUAL	
OPERATING FREQUENCY:	60 Hz	
TYPE:	CLASS A	
GROUND TRIP CURRENT:	4-6 mA	
OVERLOAD CURRENT:	90 AMP 125 VAC	
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE	
ENDURANCE OPERATIONS:	3000 OPERATIONS	
GFCI ENCLOSURE:	NEMA 3R	

MATERIAL NUMBER	ENGINEERING NUMBER	CORD TYPE	LENGTH "L"
1301530071	15053-2	12/3 SOOW	2 FT. ± 1 IN.
1301530072	15053-25	12/3 SOOW	25 FT. ± 2 IN.
1301530077	15053-50	12/3 SOOW	50 FT. ± 4 IN.

FUNCTIONAL SYMBOLS FA = 0 FC = 0 FP = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: NEW SALES DRAWING CREATED	
	DIMENSION UNITS	SCALE	EC NO: 686059	
	INCH	NTS	DRWN: PPURSUTANDEL	2021/11/02
	GENERAL TOLERANCES (UNLESS SPECIFIED)		CHK'D: DNGUYEN62	2021/12/01
DIVISIONAL SYMBOLS	ANGULAR TOL	± °	APPR: HKNEELAND	2022/01/04
	4 PLACES	±	INITIAL REVISION:	
	3 PLACES	±	DRWN: PPURSUTANDEL	2021/11/02
	2 PLACES	±	APPR: HKNEELAND	2022/01/04
1 PLACE	±	DOCUMENT NUMBER		
0 PLACES	±	1301530071		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES
			C-SIZE	130153
		MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
		SEE TABLE	GENERAL MARKET	1 OF 1

**molex**

GFCI 15A ATTACHABLE WITH DUAL SIDE OUTLET BOX

PRODUCT CUSTOMER DRAWING