

PRODUCT SPECIFICATION

FILE CODE

CATALOG LISTING

41

3AC6

CUSTOMER:

General Sales

CUST PART NUMBER

PROD. CODE NUMBER

KC-C0070

DESIGN DATA:

1. Die cast zinc bracket.
2. Stainless steel actuator rod.
3. Tapped hole in end of actuator rod.

OPTIMUM BASIC SWITCH CHARACTERISTICS:

BREAK DISTANCE _____ OF _____ RF _____

DF _____ DT _____ OT _____

MANUFACTURING INSTRUCTIONS:

ASSEMBLE ACCORDING TO DRAWING (S) (A) 3AC1

Print label / mark with catalog listing and date code, affix to bracket

With rod in either actuated position basic switch plunger must have .010" min. overtravel and with rod in free position basic switch plunger must have .005" min. release travel.

Switch must not be operated by free play of rod when rod is in the free position.

3AC6

CATALOG LISTING

ISSUE NO.	1	9	10	11	12	13	14
DATE	12Dec50	21Feb55	21Dec55	6May57	20Jul61	27Jun62	03APR09
REL. or CHANGE REFERENCE NO.	SR1426	8520	10021	Corr.	16098	17056	ECO-0038331
APPROVED BY:	ENGR. and/or TECHN. PFB/CNT	ORDER PROC'G & CONTROL JSS		PAGE 1 of 1	TYPED BY CJS	CHECKED BY 	