


UNLESS O	TOLERANCE UNLESS OTHERWISE SPECIFIED				
.X	±0.25				
.XX	±0.13				
.XXX	±0.05				

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTES:

MATERIAL:

**HOUSING:** THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

**OPERATING TEMPERATURE:** -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 40A (CURRENT)

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** 5000MΩ min.

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 1000V AC rms



PART NUMBER:

## **COMBINATION D-SUB**



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	SW REFERENCE NO.: 630 C	COMBO ASSEMBLY				
Ì	DRAWN: C.B	DATE: JAN. 01/2019				
	CHECKED:	DATE:				
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2				
	DRAWING NUMBER: 630-3W3-	250-4N6 ISSUE				

630-3W3-250-4N6



20.33 10.67

> THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

TOLERANCE UNLESS OTHERWISE SPECIFIED

.XX ±0.25 .XXX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)

2W2





5W1

○ <u>○ ○ ○</u> ○







11W1


⊙ ⊙ ⊙ ⊙ ⊙ ⊙ ⊙ ⊙






13W3










17W5










21W4









## **COMBINATION D-SUB**



THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC., AND
SHALL NOT BE REPRODUCED, OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

	DRAWN: C.B		DATE:	JAN.	01/20	19
	CHECKED:		DATE:			
;	SCALE: N.T.S		SHEET	2	OF	2
)	DRAWING NUMBER:	630-3W3-	250-4N6	;		ISSUE

630-3W3-250-4N6

630 COMBO ASSEMBLY

SW REFERENCE NO .:

PART NUMBER: