



## GA10K3MCD1 MICRO BetaCHIP (MCD) THERMISTOR PROBES

2K to 100K Ohms Resistance @25°C

0.2°C Tolerance from @ 25°C

Thermally Conductive Epoxy Coating

38 AWG Solid Nickel Bifilar with Polyester Type Insulation

Fast Time Response

Small Tip Diameter

RoHS Compliant

Micro BetaCHIP (MCD) thermistor probes are suited for applications that require rapid temperature response and where space is limited. These NTC thermistors are potted in a polyimide tube with a thermally conductive epoxy.

### FEATURES


- $\pm 0.2^\circ\text{C}$  tolerance @ +25°C
- Custom tolerances available
- Smaller than miniature BetaCURVE devices
- Rapid time response (200 milliseconds in liquids)
- Temperature range -40°C to +125°C

### APPLICATIONS

- Low volume flow sensors (liquids or gases)
- Laboratory animal research
- Peltier temperature tracking sensors
- Temperature control for bath showers
- DNA research sensors
- Medical catheters

# GA10K3MCD1 MICRO BetaCHIP (MCD) THERMISTOR PROBES

## MECHANICAL DETAILS



## PERFORMANCE SPECS

Parameters	Units	Value
Nominal Resistance at +25°C	Ohms	10,000
Resistance Tolerance at +25°C	°C	$\pm 0.2$
Alpha Value at +25°C	%/°C	-4.39
Beta Value 25/85	K	3976
Tolerance on Beta Value 25/85	%	$\pm 0.5$
Time Response in Liquids	milliseconds	200
Dissipation Constant in Still Air	mW/°C	0.3

**RESISTANCE V TEMPERATURE TABLE**

Temp. °C	Ohms
-40	336103
-39	314558
-38	294529
-37	275901
-36	258567
-35	242430
-34	227401
-33	213397
-32	200341
-31	188166
-30	176805
-29	166200
-28	156296
-27	147043
-26	138395
-25	130308
-24	122742
-23	115662
-22	109033
-21	102825
-20	97006.9
-19	91553.3
-18	86439.2
-17	81641.4
-16	77138.6
-15	72911.1
-14	68940.4
-13	65209.7
-12	61702.9
-11	58405.5
-10	55303.9
-9	52385.2
-8	49637.8
-7	47050.6
-6	44613.4
-5	42316.7
-4	40151.6
-3	38110
-2	36184
-1	34366.6
0	32650.9

Temp. °C	Ohms
1	31030.8
2	29500.5
3	28054.4
4	26687.5
5	25395
6	24172.5
7	23015.9
8	21921.2
9	20884.7
10	19903.2
11	18973.3
12	18092.2
13	17256.9
14	16464.9
15	15713.7
16	15000.9
17	14324.5
18	13682.3
19	13072.6
20	12493.3
21	11943
22	11419.9
23	10922.7
24	10449.8
<b>25</b>	<b>10000</b>
26	9572
27	9164.7
28	8777
29	8407.7
30	8056.1
31	7721
32	7401.7
33	7097.3
34	6807.1
35	6530.3
36	6266.2
37	6014.3
38	5773.8
39	5544.2
40	5325
41	5115.6

Temp. °C	Ohms
42	4915.6
43	4724.4
44	4541.7
45	4367
46	4200
47	4040.2
48	3887.4
49	3741.1
50	3601.1
51	3467
52	3338.7
53	3215.8
54	3098
55	2985.2
56	2877
57	2773.3
58	2673.9
59	2578.6
60	2487.1
61	2399.4
62	2315.2
63	2234.4
64	2156.8
65	2082.3
66	2010.8
67	1942.1
68	1876
69	1812.6
70	1751.6
71	1693
72	1636.6
73	1582.4
74	1530.2
75	1480.1
76	1431.8
77	1385.3
78	1340.6
79	1297.5
80	1256.1
81	1216.1
82	1177.7

Temp. °C	Ohms
83	1140.6
84	1104.9
85	1070.5
86	1037.3
87	1005.3
88	974.4
89	944.7
90	916
91	888.3
92	861.5
93	835.8
94	810.9
95	786.8
96	763.6
97	741.2
98	719.6
99	698.6
100	678.4
101	658.9
102	640
103	621.8
104	604.2
105	587.1
106	570.6
107	554.6
108	539.2
109	524.3
110	509.8
111	495.9
112	482.3
113	469.2
114	456.5
115	444.2
116	432.3
117	420.8
118	409.7
119	398.8
120	388.4
121	378.2
122	368.3
123	358.8
124	349.5
125	340.6

**GA10K3MCD1  
MICRO BetaCHIP (MCD) THERMISTOR PROBES**

**ORDERING INFORMATION**

<b>Part Number</b>	<b>Description</b>	<b><math>\Omega</math> @25°C</b>	<b>MOQ*</b>
GA10K3MCD1	Micro BetaCHIP thermistor probe (MCD)	10,000	1,000

\* For quantities less than MOQ (Minimum Order Quantity) contact distribution

**NORTH AMERICA**  
Tel +1 800 522 6752  
[customercare.ando@te.com](mailto:customercare.ando@te.com)

**EUROPE**  
Tel +31 73 624 6999  
[customercare.glw@te.com](mailto:customercare.glw@te.com)

**ASIA**  
Tel +86 0400 820 6015  
[customercare.chdu@te.com](mailto:customercare.chdu@te.com)

**[te.com/sensorsolutions](http://te.com/sensorsolutions)**

BetaCURVE, BetaCHIP, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, products and/or company names referred to herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2018 TE Connectivity Ltd. family of companies All Rights Reserved.