





13 12 11 10 9 8 7 6 5 4 3 2 1

J I H G F E D C B A



2	G
1	G
SHT	REV

ENC. NUMBER	ITEM NUMBER	DIM 'A'	OPTIONS	
			M3 THREADED INSERT	BOARDLOCK
A-71624-1000	051-25-1030	.092/ 2.34	YES	NO
A-71624-1001	71624-1001	.092/ 2.34	YES	YES
A-71624-1002	051-25-1032	.092/ 2.34	NO	NO
A-71624-1003	71624-1003	.125/ 3.18	YES	NO
A-71624-1013	71624-1013	.177/ 4.50	YES	NO
A-71624-1004	71624-1004	.125/ 3.18	YES	YES
A-71624-1005	71624-1005	.125/ 3.18	NO	NO

MODIFY PACKAGING
EC NO: UCP2007-0515
DRAWN: SIBARRA 2006/09/18
CHKD: BORGAN 2006/09/26
APPR: SMILLER 2006/09/27

QUALITY SYMBOLS
=0
=0

DESCRIPTION

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE IN/MM

SCALE 4:1

DESIGN UNITS INCH

THIRD ANGLE PROJECTION

DRAWN BY MOS DATE 1993/01/08

CHECKED BY BIXLER DATE 1993/01/08

APPROVED BY CAB DATE 1993/01/08

MATERIAL NO. SEE TABLE

DOCUMENT NO. SDA-71624-****

SHEET NO. 1 OF 2

.050 PITCH LFH 160 CKT VERTICAL I/O MALE SALES ASSEMBLY

MOLEX INCORPORATED

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

12 11 10 9 8 7 6 5 4 3 2 1

NOTES:

1) MATERIALS:

HOUSING: GLASS FILLED LCP (LIQUID CRYSTAL POLYMER), UL 94V-0, BLACK.
 MOLDED STICK: GLASS FILLED LCP (LIQUID CRYSTAL POLYMER), UL94V-0, BLACK.
 MALE CONTACT: PHOS. BRONZE .012±.0005 THICK.
 OUTER SHELL: LOW CARBON STEEL.
 THREADED BOARD LOCK: BRASS

2) PLATING :

TERMINAL: .000030/ 0.00076 MINIMUM GOLD IN SELECTIVE AREA;
 .000100/ 0.00254 MINIMUM TIN IN SELECTIVE AREA;
 OVER NICKEL UNDERPLATE OVERALL.

OUTER SHELL: .000100/ 0.00254 MINIMUM BRIGHT NICKEL
 OVER COPPER FLASH OPTIONAL.



BOARDLOCK: .000150-.000200/ 0.00381-0.00508 TIN
 OVER .000050/ 0.00127 MINIMUM NICKEL.

3) THIS PART CONFORMS TO MOLEX PRODUCT SPECIFICATION PS-71626.

4) PACKAGING SPECIFICATION PK-70873-297 APPLIES.

NOTE FOR LEAD FREE CONVERSION:

THE PRIMARY SHIPPING CARTON WILL BE
 LABELED *COMPLIANT TO RoHS DIRECTIVE
 2002/95/EC AND ELV ANNEX II OF
 DIRECTIVE 2000/53/EC*. CARTONS
 WITHOUT THIS LABEL MAY CONTAIN
 PRODUCT WITH LEAD.



PANEL CUT-OUT DIMENSIONS

ALL TOLERANCES ±.003/ 0.08
 UNLESS OTHERWISE STATED.

MODIFY PACKAGING EC NO: UCP2007-0515 DRWNS:IBARRA 2006/09/18 CHKD:BMORGAN 2006/09/26 APPR:SMILLER 2006/09/27 REVISION DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2°	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
	=0 ∇=0		IN/MM	2:1	INCH	☉ □ THIRD ANGLE PROJECTION	
				TITLE	.050 PITCH LFH 160 CKT VERTICAL I/O MALE SALES ASSEMBLY		
				DRAWN BY DATE SCHMIDGALL 1993/01/08 CHECKED BY DATE BIXLER 1993/01/08 APPROVED BY DATE CAB 1993/01/08 MATERIAL NO. DOCUMENT NO.	MOLEX INCORPORATED SDA-71624-****	SHEET NO.	2 OF 2

DRAFT WHERE APPLICABLE
 MUST REMAIN
 WITHIN DIMENSIONS

SEE TABLE

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION