



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-------------------------|
| L | 7.37mm +/-0.25mm |
| H | 7.37mm +/-0.25mm |
| T | 2.29mm +/-0.25mm |
| S | 5.08mm +/-0.38mm |
| LL | 31.75mm MIN |
| F | 0.635mm +0.102/-0.051mm |

| Packaging Specifications | |
|--------------------------|--------------------|
| Packaging | T&R, 305mm, Type I |
| Packaging Quantity | 1500 |

| General Information | |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| Series | LDD Comm COG |
| Style | Radial |
| Features | Commercial |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov . |
| SCIP Number | 8c864fd1-202b-4ce7-85fd-56c9e19121ad |
| Termination | Lead (SnPb) |
| Failure Rate | N/A |
| AEC-Q200 | No |

| Specifications | |
|---------------------------------|---------------|
| Capacitance | 8200 pF |
| Capacitance Tolerance | 5% |
| Voltage DC | 100 VDC |
| Dielectric Withstanding Voltage | 250 VDC |
| Temperature Range | -55/+125°C |
| Temperature Coefficient | COG |
| Dissipation Factor | 0.1% 1kHz 25C |
| Insulation Resistance | 122 MOhms |