

**TITLE**

**698MHZ-6GHZ WIDE BAND ANTENNA**

**TABLE OF CONTENTS**

- 1.0 SCOPE**
- 2.0 PRODUCT DESCRIPTION**
- 3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS**
- 4.0 RATINGS**
- 5.0 PERFORMANCE**
- 6.0 TEST GROUPINGS**
- 7.0 PACKING**

THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REVISION DESCRIPTION	REMOVED OBSOLETE PART NUMBERS AND THEIR RESPECTIVE TABLES AS PER PCN#510806 REQUEST.			<b>PS FOR 698MHZ-6GHZ WIDE BAND ANTENNA</b>			
CHANGE NO.	733771						
REVISED BY	LIKITV	DATE	2023/01/05	DOC TYPE	DOC TYPE DESCRIPTION	DOC PART	SERIES
REV APPR BY	GGA	DATE	2023/02/24	PS	PRODUCT SPECIFICATION WORD	PS	146234
INITIAL RELEASE				CUSTOMER		DOCUMENT NUMBER	
INITIAL DRWN	KCHENG06	DATE	2017/11/20	<b>1462340100</b>		<b>A1</b>	1 OF 6
INITIAL APPR	XJSONG	DATE	2017/11/21				

**698MHZ-6GHZ WIDE BAND ANTENNA**

**1.0 SCOPE**

This Product Specification covers the mechanical, electrical and environmental performances requirements and test methods for 698MHz-6GHz Wide Band Antenna.

**2.0 PRODUCT DESCRIPTION**

**2.1 PRODUCT NAME AND SERIES NUMBER (S)**

Product name: 698MHz-6GHz Wide Band Antenna.

**2.2 Design and Construction**

Antenna shall be of the design, construction and physical dimensions specified on the applicable sales drawing.

**2.3 Materials**

- a) Flex: Refer to sales drawings SD of 1462340100.
- b) Cable Line: Refer to sales drawings SD of 1462340100.
- c) Connector: Refer to sales drawings SD of 1462340100.

**3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS**

See drawings and other sections of this specification for the relevant reference documents. In cases where the specification differs from the drawings, the drawings take precedence.

**4.0 RATINGS**

**4.1 RF POWER**

2 WATTS

**4.2 TEMPERATU**

- Operating : -30°C to 85°C
- Storage : -40°C to 95°C

**4.3 HUMIDITY**

- Operating : -30°C to 85°C
- 30°C to 50°C, 85%RH or less
- 50°C to 85°C, 60%RH or less
- Storage : -40°C to 95°C
- 40°C to 50°C, 85%RH or less
- 50°C to 95°C, 60%RH or less

THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REVISION DESCRIPTION		REMOVED OBSOLETE PART NUMBERS AND THEIR RESPECTIVE TABLES AS PER PCN#510806 REQUEST.		<b>PS FOR 698MHZ-6GHZ WIDE BAND ANTENNA</b>			
CHANGE NO.	733771						
REVISED BY	LIKITV	DATE	2023/01/05	DOC TYPE	DOC TYPE DESCRIPTION	DOC PART	SERIES
REV APPR BY	GGA	DATE	2023/02/24	PS	PRODUCT SPECIFICATION WORD	PS	146234
INITIAL RELEASE				CUSTOMER		DOCUMENT NUMBER	
INITIAL DRWN	KCHENG06	DATE	2017/11/20	<b>1462340100</b>		<b>A1</b>	2 OF 6
INITIAL APPR	XJSONG	DATE	2017/11/21				

## 5.0 PERFORMANCE

### 5.1 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 50mm (1462340050)

DESCRIPTION	TEST CONDITION	REQUIREMENTS		
Frequency Range	698MHz-960MHz / 1.5GHz~6GHz	698~960MHz	1.5~2.7GHz	2.7GHz~6GHz
Return Loss	Antenna with 100mm long, 1.13mm diameter micro coaxial cable in free space Measured by VNA5071C	<-4dB	< -5 dB	
Peak Gain (Max)	Measure antenna in free space through OTA chamber	1.9dBi	2.85dBi	5.2dBi
Total Efficiency	Measure antenna in free space through OTA chamber	>70%	>70%	>70%
Polarization	Measure antenna in free space through OTA chamber	Linear		
Input Impedance	Measure antenna in free space through VNA E5071C	50 Ohms		

### 5.2 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 100mm (1462340100)

DESCRIPTION	TEST CONDITION	REQUIREMENTS		
Frequency Range	698MHz-960MHz / 1.5GHz~6GHz	698~960MHz	1.5~2.7GHz	2.7GHz~6GHz
Return Loss	Antenna with 100mm long, 1.13mm diameter micro coaxial cable in free space Measured by VNA5071C	< -4 dB	< -5 dB	
Peak Gain (Max)	Measure antenna in free space through OTA chamber	1.8dBi	2.8dBi	5.0dBi
Total Efficiency	Measure antenna in free space through OTA chamber	>70%	>70%	>70%
Polarization	Measure antenna in free space through OTA chamber	Linear		
Input Impedance	Measure antenna in free space through VNA E5071C	50 Ohms		

THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REVISION DESCRIPTION	REMOVED OBSOLETE PART NUMBERS AND THEIR RESPECTIVE TABLES AS PER PCN#510806 REQUEST.			<b>PS FOR 698MHZ-6GHZ WIDE BAND ANTENNA</b>			
CHANGE NO.	733771						
REVISED BY	LIKITV	DATE	2023/01/05	DOC TYPE	DOC TYPE DESCRIPTION	DOC PART	SERIES
REV APPR BY	GGA	DATE	2023/02/24	PS	PRODUCT SPECIFICATION WORD	PS	146234
INITIAL RELEASE				CUSTOMER	DOCUMENT NUMBER	REVISION	SHEET
INITIAL DRWN	KCHENG06	DATE	2017/11/20		<b>1462340100</b>	<b>A1</b>	3 OF 6
INITIAL APPR	XJSONG	DATE	2017/11/21				



# PRODUCT SPECIFICATION

## 5.3 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 150mm (1462340150)

DESCRIPTION	TEST CONDITION	REQUIREMENTS		
Frequency Range	698MHz-960MHz / 1.5GHz~6GHz	698~960MHz	1.5~2.7GHz	2.7GHz~6GHz
Return Loss	Antenna with 100mm long, 1.13mm diameter micro coaxial cable in free space Measured by VNA5071C	< -4 dB	< -5 dB	
Peak Gain (Max)	Measure antenna in free space through OTA chamber	1.7dBi	2.65dBi	4.8dBi
Total Efficiency	Measure antenna in free space through OTA chamber	>69%	>68%	>67%
Polarization	Measure antenna in free space through OTA chamber	Linear		
Input Impedance	Measure antenna in free space through VNA E5071C	50 Ohms		

## 5.4 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 200mm (1462340200)

DESCRIPTION	TEST CONDITION	REQUIREMENTS		
Frequency Range	698MHz-960MHz / 1.5GHz~6GHz	698~960MHz	1.5~2.7GHz	2.7GHz~6GHz
Return Loss	Antenna with 100mm long, 1.13mm diameter micro coaxial cable in free space Measured by VNA5071C	< -4 dB	< -5 dB	
Peak Gain (Max)	Measure antenna in free space through OTA chamber	1.6dBi	2.5dBi	4.6dBi
Total Efficiency	Measure antenna in free space through OTA chamber	>68%	>66%	>64%
Polarization	Measure antenna in free space through OTA chamber	Linear		
Input Impedance	Measure antenna in free space through VNA E5071C	50 Ohms		

THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REVISION DESCRIPTION	REMOVED OBSOLETE PART NUMBERS AND THEIR RESPECTIVE TABLES AS PER PCN#510806 REQUEST.			<b>PS FOR 698MHZ-6GHZ WIDE BAND ANTENNA</b>			
CHANGE NO.	733771						
REVISED BY	LIKITV	DATE	2023/01/05	DOC TYPE	DOC TYPE DESCRIPTION	DOC PART	SERIES
REV APPR BY	GGA	DATE	2023/02/24	PS	PRODUCT SPECIFICATION WORD	PS	146234
INITIAL RELEASE				CUSTOMER		DOCUMENT NUMBER	
INITIAL DRWN	KCHENG06	DATE	2017/11/20	<b>1462340100</b>		<b>A1</b>	4 OF 6
INITIAL APPR	XJSONG	DATE	2017/11/21				

## 5.5 CABLE LOSS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENTS			
5.7.1	Frequency Range	698MHz~6GHz	698MHz~960MHz	1.5GHz~3GHz	3GHz~5GHz	5GHz~6 GHz
5.7.2	Attenuation	1m cable measured by VNA5071C	≤1.8dB/m	≤3dB/m	≤4dB/m	≤5dB/m

## 5.6 CABLE LENGTH AFFECT THE ANTENNA PERFORMANCE

Balance antenna resonance is insensitive by cable's length, but the cable's loss will affect the total efficiency. Refer to 5.7

## 5.7 MECHANICAL REQUIREMENTS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
5.7.1	Pull test	Test machine :Max intelligent load tester Stick the Flex antenna in a PC block, pull cable in horizontal direction.	Pull force >8N

## 5.8 ENVIRONMENTAL REQUIREMENTS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
5.8.1	Temperature /Humidity cycling	Test condition: 1) The device under test is kept for 30 mins in an environment with a temperature of -40 °C 2) Kept for 4 Hours in an environment with a temperature of 85 degrees and a relative humidity of 95%. 3) Kept for 2 Hours in an environment with a temperature of 125 degrees and a relative humidity of 95%. 4) The cycle is repeated until a total of 40 cycles have been completed. Hereafter the conditions are stabilized at room temperature.	1) Parts should meet RF spec before and after test. 2) No cosmetic problem
5.8.2	Temperature Shock	Test condition: The device under test at -40 °C⇌125 °C by 100 cycles, Dwell of 30 mins, transition time between Dwell 30 secs (~ 61 mins / cycle ) and each item should be measured after exposing them in normal temperature and humidity for 24 h.	1) Parts should meet RF spec before and after test. 2) No cosmetic problem

THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REVISION DESCRIPTION	REMOVED OBSOLETE PART NUMBERS AND THEIR RESPECTIVE TABLES AS PER PCN#510806 REQUEST.			<b>PS FOR 698MHZ-6GHZ WIDE BAND ANTENNA</b>			
CHANGE NO.	733771						
REVISED BY	LIKITV	DATE	2023/01/05	DOC TYPE	DOC TYPE DESCRIPTION	DOC PART	SERIES
REV APPR BY	GGA	DATE	2023/02/24	PS	PRODUCT SPECIFICATION WORD	PS	146234
INITIAL RELEASE				CUSTOMER		DOCUMENT NUMBER	
INITIAL DRWN	KCHENG06	DATE	2017/11/20		<b>1462340100</b>	<b>A1</b>	5 OF 6
INITIAL APPR	XJSONG	DATE	2017/11/21				

5.8.3	High Temperature	Test condition: 1) Temperature:125°C, time:1008hours 2) There is no substantial obstruction to air flow across and around the samples, and the samples are not touching each other	1) Parts should meet RF spec before and after test. 2) No cosmetic problem
5.8.4	Salt mist test	1. Test condition: The device under test is exposed to a spray of a 5% (by volume) resolution of NaCl in water for 2 hours. Thereafter the device under test is left for 1 week in room temperature at a relative humidity of 95%. The cycle is repeated until a total of 2 cycles have been completed. Here after the conditions are stabilized at room temperature.	1) Parts should meet RF spec before and after test. 2) No visible corrosion. Discoloration accept.

The meaning of text “**No Cosmetic Problem**” in the table above is:

- a. No soldering problem
- b. No adhesion problem of glue

**6.0 TEST GROUPINGS**

Test Item	Description	Group1	Group2	Group3	Group4	Group5
5.9.1	Pull test	X				
5.10.1	Temperature /Humidity cycling		X			
5.10.2	Temperature Shock			X		
5.10.3	High Temperature				X	
5.10.4	Salt mist test					X
	Sample Quantity	5	5	5	5	5

**7.0 PACKAGING**

Refer to the Molex related packaging drawings of 1462340100.

THIS DOCUMENT CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REVISION DESCRIPTION		REMOVED OBSOLETE PART NUMBERS AND THEIR RESPECTIVE TABLES AS PER PCN#510806 REQUEST.		<b>PS FOR 698MHZ-6GHZ WIDE BAND ANTENNA</b>					
CHANGE NO.	733771								
REVISED BY	LIKITV	DATE	2023/01/05	DOC TYPE	DOC TYPE DESCRIPTION		DOC PART	SERIES	
REV APPR BY	GGA	DATE	2023/02/24	PS	PRODUCT SPECIFICATION WORD		PS	146234	
INITIAL RELEASE				CUSTOMER		DOCUMENT NUMBER		REVISION	SHEET
INITIAL DRWN	KCHENG06	DATE	2017/11/20			<b>1462340100</b>		<b>A1</b>	6 OF 6
INITIAL APPR	XJSONG	DATE	2017/11/21						