

## Specification Sheet

Part Number: MB50F4



Screw Mount Cable Tie Base, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66, Black, 250/pkg

<b>Article Number</b>	151-28501
<b>Type</b>	MB5
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Compact size fits most mounting applications.</li><li>•Simple to install with a screw or rivet.</li><li>•Single hole attachment with two-way entry for cable tie.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	These cable tie mounts are compact in size. They are designed for simple yet robust installation. They pair with a cable tie for mounting applications including telecom equipment, switchgear and control cabinets.
<b>Short Description</b>	Screw Mount Cable Tie Base, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66, Black, 250/pkg

Global Part Name

MB5-PA66-BK

Length L (Imperial)

1.49

Length L (Metric)

37.7

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

1.49

Width W (Metric)

37.7

Cable Ties

T18 - T150

Height H (Imperial)

.25

Height H (Metric)

6.20

Cable Tie Width Max (Imperial)

0.35

Cable Tie Width Max (Metric)

8.9

Mounting Hole Diameter D (Imperial)

0.19

Mounting Hole Diameter D (Metric)

4.8 mm

Mounting Hole Diameter D Max (Metric)

4.8

Mounting Hole Centers (Imperial)

1.0

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	250
<b>Package Quantity (Metric)</b>	250
<b>Customs Number</b>	3926909988