

## T350H476K010AT7301

Aliases (T350H476K010ATTR)

T350, Tantalum, MnO<sub>2</sub> Tantalum, Commercial Grade, 47 uF, 10%, 10 VDC, Radial, Solid Tantalum, Conformal, Dipped, Lead Spacing = 2.54mm



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| D  | 7.6mm            |
| H  | 10.2mm           |
| S  | 2.54mm +/-0.38mm |
| LL | 12.7mm +/-1.26mm |
| F  | 0.5mm +/-0.05mm  |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, 305mm |
| Packaging Quantity | 800        |

### General Information

|             |   |
|-------------|---|
| Series      | T350                                      |
| Dielectric  | MnO <sub>2</sub> Tantalum                 |
| Style       | Radial                                    |
| Description | Radial, Solid Tantalum, Conformal, Dipped |
| Features    | Low Leakage                               |
| RoHS        | Yes                                       |
| Termination | Tin                                       |
| AEC-Q200    | No  |
| Notes       | Longest Lead Is Positive.                 |

### Specifications

|                       |  |
|-----------------------|--|
| Capacitance           | 47 uF  |
| Capacitance Tolerance | 10%  |
| Voltage DC            | 10 VDC (85C), 7 VDC (125C), 0.1 VDC (125C Reverse) |
| Temperature Range     | -55/+125°C   |
| Dissipation Factor    | 6%   |
| Leakage Current       | 3.8 uA   |