



Expertise Applied | Answers Delivered

Search All [input] Search

Home > Products > Switches



8640 - Air Pressure Switches Series



Series:

Questions? [Contact Littelfuse Support](#)



For dependable operation of low air pressure warning systems.
Sealed contact design prevents short circuits caused by moisture and contaminants.
Normally On (Contacts open at rising pressure)
Mounting stem: 1/4" -18 dryseal thread.
Normally closed, open at 56 - 74 psi (386.1 – 510.2 kPa).
8-32 stud terminal.

Replaces Chrysler 1787025, 1788700, Delco 3750911, 3929518, Ford B6Q, B8Q-18737A, C5TZ-2A574A, International 194702-R91, Motorcraft SW-377.

Connect with Littelfuse

Sign up to receive special offers and news

For more details about how we use your information, check our [Privacy Statement](#).

[Linked In](#) [Littelfuse Google Plus](#) [Facebook](#)
[Twitter](#) [Littelfuse YouTube](#) [Weibo](#) [RSS](#)



About Littelfuse

- [About Littelfuse](#)
- [Conflict Free Statement](#)
- [History](#)
- [Investor Relations](#)
- [Legal](#)
- [Press Room](#)
- [Privacy Statement](#)
- [Supply Chain Transparency](#)
- [Website Feedback](#)

Explore Littelfuse

- [Capabilities Brochures](#)
- [Careers](#)
- [Check Distributor Stock](#)
- [Competitor Cross Reference](#)
- [Industries](#)
- [Order Samples](#)
- [Products](#)
- [Services](#)

Technical Resources

- [Application Designs](#)
- [Education](#)
- [FAQs](#)
- [iDesign™](#)
- [Littelfuse University](#)
- [Product Catalogs](#)
- [Quality Documents](#)
- [Technical Documents](#)