



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Without Plating
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours
- Mass : 19.6 g ± 10%

| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.25±0.2      |
| PP                  | 4.93±0.2      |
| R1                  | 26.97         |
| R2                  | 24.61         |
| S                   | 33.3±0.3      |
| V                   | 20.83+0/-1.25 |
| W                   | 2.1/2.5       |
| Z                   | 31.5 Max      |
| VV THREAD           | M25x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D017X75PNL**

|                |                                       |                                |   |
|----------------|---------------------------------------|--------------------------------|---|
| B              | 17-04-17                              | Drawing Update                 |   |
| ISS            | DATE                                  | Latest modification - by       | MOD N°  |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Composite Receptacle 8D series</b> |                                |   |
| SCALE          | NA                                    | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>A3</b>                             |                                | SOURIAU DRG N°<br><b>8D017X75PNL-C</b>  |
|                |                                       |                                | SHEET<br>1/2  |

|                |                          |   |   |    |                                 |    |   |   |   |                        |
|----------------|--------------------------|---|---|----|---------------------------------|----|---|---|---|------------------------|
| BASIC SERIES:  | 8D                       | 0 | - | 17 | X                               | 75 | P | N | L | Delivered W/O Contacts |
| SHELL TYPE :   | Square Flange Receptacle |   |   |    | ORIENTATION : N                 |    |   |   |   |                        |
| CONTACT TYPE : | Standard Crimp Contact   |   |   |    | CONTACT TYPE : PIN(500 Matings) |    |   |   |   |                        |
| SHELL SIZE :   | 17                       |   |   |    | CONTACT LAYOUT : 17-75          |    |   |   |   |                        |
| PLATING :      | X = Without Plating      |   |   |    |                                 |    |   |   |   |                        |

Contact Layout

75



2#8 Triax

| 17-75 |   |       |
|-------|---|-------|
| Ctc   | X | Y     |
| A     | 0 | 4.75  |
| B     | 0 | -4.75 |

Panel Cutout



Max. thickness panel for receptacle: Type 0: front mounting = 3.2 mm, rear mounting = 2.5 mm

| Dim | Nominal    |
|-----|------------|
| ØA  | 30.96 min  |
| ØAA | 25.81 min  |
| R1  | 26.97      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D017X75PNL

|                |                                     |                            |   |
|----------------|-------------------------------------|----------------------------|---|
| B              | 17-04-17                            | Drawing Update             |   |
| ISS            | DATE                                | Latest modification - by   | MOD N°  |
| Designed By:   |                                     | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Composite Receptacle 8D series      |                            |   |
| SCALE          |                                     | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                     | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>              |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D017X75PNL-C</b> |                            | SHEET 2/2   |