

ProductSKU: C1363.38.90
ProductDescription: SpeakerWire,ULListed(Wires,Misc.)120Vmax.,No.ofConductors:2,GaugeSize(AWG):12,Conductor/Strands:65/30,Jacket:PremiumGradePVC-Clear-500Ft.Reel
ProductCategory: Electronics-GeneralPurposeCable-SpeakerWire-Clear

**ProductConstruction:**

Conductor: • 24thru 12AWGfully-annealed 1bare, 1tinstrandedcopperperASTMB-174
Insulation/Jacket: • PremiumgradePVC

ProductSpecification:

No.ofConductors: • 2
ConductorSize(AWG): • 12
Conductor/Strands: • 65/30
JacketColor: • Clear
NominalInsulationThickness (in): • 0.030
NominalInsulationThickness (mm): • 0.76
NominalOutsideDiameter(in): • 0.160x0.335
NominalOutsideDiameter (mm): • 4.06x8.51
StandardPackaging: • 500'Non-returnableWoodReels
StandardPackageQuantity: • 1
UPC#: • 079407762576
Put-up: • 500
SCC-14: • 50079407762577
Cube: • 1494.425
WeightPerUnitofMeasure: • .2929
ColorOption: • Clear

ProductInformation:

Applications:

- Hi-fi and stereo speaker wire
- Jukeboxes
- Lamps
- Radios
- Suggested voltage rating: 120 Volts

Compliances:

- UL Wires Misc. (UL: 120V)

Packaging:

- 1000' (305m) Spools
- 500' (152m) Spools
- Other put-ups available - consult Customer Service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[4' Carol Brand Electrical Wire Center](#)

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL
BRAND**