

Caps Fingergrip for Holder FEU, FAU, FAC



250 VAC · 4 W · 600 VAC/DC · 20 A (UL/CSA)

See below:
[Approvals and Compliances](#)

References

Mating Cap to [FAC](#); [FAU](#); [FEU](#)

Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#), [Microsite](#)

Technical Data

| | |
|------------------------------|------------------------------------|
| Fuse-Link | 5 x 20 or 6.3 x 32 mm |
| Rated Voltage | 250 VAC (VDE), 600 VAC/DC (UL/CSA) |
| Rated current | 10 A (VDE), 20 A (UL/CSA) |
| Rated Power Acceptance IEC | 4 W @ Ta 23 °C |
| Degree of Protection | IP 40 |
| Admissible Ambient Air Temp. | -40 °C to 85 °C |
| Material: Cap | Thermoset, UL 94V-0 |
| Storage Conditions | 0 °C to 60 °C, max. 70% r.h. |




Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Product standards

Product standards that are referenced

| Organization | Design | Standard | Description |
|-------------------------------------------------------------------------------------|-----------------------|----------------------|----------------------------------------------------------------|
|  | Designed according to | IEC 60127-6 | Miniature fuses. Part 6. Fuse-holders for miniature fuse-links |
|  | Designed according to | UL 4248-1 | Fuseholder general requirements |
|  | Designed according to | CSA C22.2 no. 4248.1 | Fuseholder general requirements |




Application standards


Application standards where the product can be used



| Organization | Design | Standard | Description |
|-------------------------------------------------------------------------------------|--------------------------------|--------------|-------------------------------------------------------------------------------------------------|
|  | Designed for applications acc. | IEC/UL 60950 | IEC 60950-1 includes the basic requirements for the safety of information technology equipment. |

Compliances

The product complies with following Guide Lines

| Identification | Details | Initiator | Description |
|----------------------------------------------------------------------------------|------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | RoHS | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/836 |
|  | China RoHS | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS. |
|  | REACH | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force. |



Dimension [mm]  40 mm



Variant 0031.1667

Variant 0031.1741

All Variants

| Cap | Fuse-Link | Degree of Protection | Order Number |
|------------|------------|----------------------|----------------------------------------------------------------------------------------------|
| Fingergrip | 6.3 x 32mm | IP40 | 0031.1667  |
| Fingergrip | 5 x 20mm | IP40 | 0031.1741  |

 Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging Unit Plastic Bag (100 pcs.)